

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Negative Photoresist AR-N 4240

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Intermediate for electronic industry

1.3 Details of the supplier of the safety data sheet

Company name: Allresist
Gesellschaft für chemische Produkte zur Mikrostrukturierung mbH
Street/POB-No.: Am Biotop 14
Postal Code, city: 15344 Strausberg
Germany
WWW: www.allresist.de
E-mail: info@allresist.de
Telephone: +49 (0)33 41-35 93-0
Telefax: +49 (0)33 41-35 93-29
Dept. responsible for information:
Frau Feldt, Email: doerte.feldt@allresist.de

1.4 Emergency telephone number

Telephone: +49 (0)33 41-35 93-0
Only available during office hours.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.
(EUH019) May form explosive peroxides.
Eye Irrit. 2; H319 Causes serious eye irritation.
Carc. 2; H351 Suspected of causing cancer.
STOT SE 3; H335 May cause respiratory irritation.
(EUH066) Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 2 of 12

2.2 Label elements

Labelling (CLP)



Signal word:

Warning

Hazard statements:	H226	Flammable liquid and vapour.
	H319	Causes serious eye irritation.
	H335	May cause respiratory irritation.
	H351	Suspected of causing cancer.
	EUH019	May form explosive peroxides.
	EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapours.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Special labelling

Text for labelling:

Contains 1,4-Dioxane and 2-Methoxy-1-methylethyl acetate.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 3 of 12

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.
Special danger of slipping by leaking/spilling product.

SECTION 3: Composition / information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation:

Mixture of the following listed substances with safe additions

Hazardous ingredients:

Ingredient	Designation	Content	Classification
EC No. 203-603-9 CAS 108-65-6	2-Methoxy-1-methylethyl acetate	30 - 60 %	CLP: Flam. Liq. 3; H226.
EC No. 204-661-8 CAS 123-91-1	1,4-Dioxane	10 - 25 %	CLP: Flam. Liq. 2; H225. Eye Irrit. 2; H319. Carc. 2; H351. STOT SE 3; H335. (EUH019). (EUH066).
EC No. 270-931-7 CAS 68510-93-0	Naphthoquinone diazide	5 - 10 %	CLP: Aquatic Chronic 3; H412.
EC No. 215-293-2 CAS 1319-77-3	Cresol-isomers	< 0.25 %	CLP: Acute Tox. 3; H301. Acute Tox. 3; H311. Skin Corr. 1B; H314.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:	First aider: Pay attention to self-protection! Immediately remove any contaminated clothing, shoes or stockings.
In case of inhalation:	Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical aid in case of troubles.
Following skin contact:	Remove residues with soap and water. Consult physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.
After swallowing:	Never give anything by mouth to an unconscious person. Rinse mouth immediately and drink plenty of water. Do not induce vomiting. Seek medical attention.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 4 of 12

4.2 Most important symptoms and effects, both acute and delayed

Nausea, vomiting, headache, dizziness, CNS disorders, unconsciousness.

Absorption can lead to kidney and liver damage.

In case of inhalation:

central nervous system depression, Cough and shortage of breath. Pulmonary edema is possible. Symptoms may occur with delay.

In case of ingestion: May be harmful if swallowed.

Other symptoms: Nausea, vomiting, central nervous system depression.

After contact with skin:

Prolonged/repetitive skin contact may cause skin defatting or dermatitis. Danger of cutaneous absorption. May cause irritations.

After eye contact: Reddening

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Decontamination.

In the event of pulmonary irritation treat initially with dexamethasone - dosing aerosol.

Subsequent observance for pneumonia and lung oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Extinguishing powder, water fog or carbon dioxide.

In case of large fires alcohol resistant foam or water fog.

Extinguishing media which must not be used for safety reasons:

High power water jet.

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour. On contact with air, potentially explosive mixtures may develop. Vapours may proceed on the ground over great distances and cause fire and backflashes.

In case of fire may be liberated: Nitrogen oxides (NO_x), carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information: Hazchem-Code: •3Y

Do not expose to high temperature. Danger of bursting and explosion. Use fine water spray to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 5 of 12

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Avoid contact with the substance. Do not breathe vapours. Wear protective equipment. Provide adequate ventilation. Keep unprotected people away.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion! In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Beware of reignition. Thoroughly clean surrounding area. In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information: Use explosion-proof equipment and non-sparking tools/utensils. Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.

Do not breathe vapours. Avoid contact with skin, eyes, and clothing.

Wear protective equipment.

Do not allow containers to stand open. Handle and open container with care.

Precautions against fire and explosion:

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Use grounding equipment. Use only explosion-protected equipment/instruments. Do not weld. Vapours can form explosive mixtures with air. May form explosive peroxides.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry. Keep only in the original container.

Keep away from sources of ignition and heat. Protect from direct sunlight.

Store containers in upright position. Explosion protection required.

Qualified materials: steel, polypropylene.

Unsuitable materials: Copper, zinc.

Storage temperature: 14 °C up to 20 °C.

Hints on joint storage:

Do not store together with combustible or self-igniting materials or any highly flammable solids. Keep away from food, drink and animal feedingstuffs.

Storage class:

3 = Flammable liquids

7.3 Specific end use(s)

No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 6 of 12

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
108-65-6	2-Methoxy-1-methylethyl acetate	Europe: IOELV: STEL	550 mg/m ³ ; 100 ppm (May be absorbed through the skin.)
		Europe: IOELV: TWA	275 mg/m ³ ; 50 ppm (May be absorbed through the skin.)
		Great Britain: WEL-STEL	548 mg/m ³ ; 100 ppm
		Great Britain: WEL-TWA	274 mg/m ³ ; 50 ppm
		Ireland: 15 minutes	550 mg/m ³ ; 100 ppm (May be absorbed through the skin.)
123-91-1	1,4-Dioxane	Ireland: 8 hours	275 mg/m ³ ; 50 ppm (May be absorbed through the skin.)
		Europe: IOELV: TWA	73 mg/m ³ ; 20 ppm
		Great Britain: WEL-TWA	73 mg/m ³ ; 20 ppm
1319-77-3	Cresol-isomers	Ireland: 8 hours	73 mg/m ³ ; 20 ppm
		Europe: IOELV: TWA	22 mg/m ³ ; 5 ppm
		Great Britain: WEL-TWA	22 mg/m ³ ; 5 ppm
		Ireland: 8 hours	22 mg/m ³ ; 5 ppm

8.2 Exposure controls

When aerosols and vapours form: Withdraw by suction.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. Use filter type A (= against vapours of organic substances) according to EN 14387.

Hand protection: Protective gloves according to EN 374.
Glove material: butyl caoutchouc (butyl rubber) (0,7 mm).
Breakthrough time: >480 min.
Unsuitable materials: natural rubber, nitrile rubber.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to EN 166.

Body protection: Flame retardant, antistatic and chemical resistant protective clothing.

General protection and hygiene measures:

Use only non-sparking tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Avoid contact with skin, eyes, and clothing. Change contaminated clothing.

Do not breathe vapour/aerosol. Wear protective equipment.

Have eye wash bottle or eye rinse ready at work place.

Wash hands before breaks and after work.

When using do not eat, drink or smoke.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 7 of 12

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Form: liquid Colour: brown-red
Odour:	ester-like
Odour threshold:	no data available
pH value:	no data available
Melting point/freezing point:	no data available
Initial boiling point and boiling range:	101 - 102 °C (1,4-Dioxane)
Flash point/flash point range:	32 °C (c.c.)
Evaporation rate:	no data available
Flammability:	Flammable liquid and vapour.
Explosion limits:	LEL (Lower Explosion Limit): 1.20 Vol-% (2-Methoxy-1-methylethyl acetate) UEL (Upper Explosive Limit): 25.20 Vol-% (1,4-Dioxane)
Vapour pressure:	at 20 °C: 41 hPa (1,4-Dioxane)
Vapour density:	no data available
Density:	at 20 °C: approx. 1 g/mL
Water solubility:	at 20 °C: partially soluble
Partition coefficient: n-octanol/water:	no data available
Auto-ignition temperature:	no data available
Thermal decomposition:	no data available
Viscosity, dynamic:	no data available
Explosive properties:	On contact with air, potentially explosive mixtures may develop. May form explosive peroxides.
Oxidizing characteristics:	no data available

9.2 Other information

Ignition temperature:	300 °C (1,4-Dioxane)
Additional information:	Information about 2-Methoxy-1-methylethyl acetate: Saturation concentration at 20 °C: 26.6 g/m ³ Relative vapour density (air=1): 4.56

SECTION 10: Stability and reactivity

10.1 Reactivity

Flammable liquid and vapour. On contact with air, potentially explosive mixtures may develop.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Do not expose to high temperature. Danger of bursting and explosion.
May form explosive peroxides.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 8 of 12

10.4 Conditions to avoid

Access of air and oxygen (Peroxide formation!)
Keep away from heat. Protect from direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents, alkalis. Attacks many plastics and rubbers.

10.6 Hazardous decomposition products

In case of fire may be liberated: Nitrogen oxides (NO_x), carbon monoxide and carbon dioxide.

Thermal decomposition: no data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological effects:

- Acute toxicity (oral): Lack of data.
- Acute toxicity (dermal): Lack of data.
- Acute toxicity (inhalative): Lack of data.
- Skin corrosion/irritation: Lack of data.
- Eye damage/irritation: Eye Irrit. 2; H319 = Causes serious eye irritation.
- Sensitisation to the respiratory tract: Lack of data.
- Skin sensitisation: Lack of data.
- Germ cell mutagenicity/Genotoxicity: Lack of data.
- Carcinogenicity: Carc. 2; H351 = Suspected of causing cancer.
- Reproductive toxicity: Lack of data.
- Effects on or via lactation: Lack of data.
- Specific target organ toxicity (single exposure): STOT SE 3; H335 = May cause respiratory irritation.
- Specific target organ toxicity (repeated exposure): Lack of data.
- Aspiration hazard: Lack of data.

Carcinogenic, germ cell mutagen and reproduction effects:

Carc. Cat. 3 - Limited evidence of a carcinogenic effect.

Other information:

Information about 2-Methoxy-1-methylethyl acetate:

LD50 Rat, oral: 8532 mg/kg.

LD50 Rabbit, dermal: 7500 mg/kg.

Systemic effects: Drowsiness, cyanosis (blue coloured blood), unconsciousness, narcosis. damage of kidneys.

Information about Cresol-isomers:

LD50 Rat, oral: 1454 mg/kg.

LD50 Rabbit, dermal: 242 mg/kg.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 9 of 12

Symptoms

Nausea, vomiting, headache, dizziness, CNS disorders, unconsciousness.

Absorption can lead to kidney and liver damage.

In case of inhalation:

central nervous system depression, Cough and shortage of breath. Pulmonary edema is possible. Symptoms may occur with delay.

In case of ingestion: May be harmful if swallowed.

Other symptoms: Nausea, vomiting, central nervous system depression.

After contact with skin:

Prolonged/repetitive skin contact may cause skin defatting or dermatitis. Danger of cutaneous absorption. May cause irritations.

After eye contact: Reddening

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Information about Naphthoquinone diazide:

Fish toxicity:

LC50 zebrafish 22 - 50 mg/L/96h.

Information about 2-Methoxy-1-methylethyl acetate:

Daphnia toxicity:

EC50 Daphnia magna (Big water flea): 408 mg/L/48h.

Fish toxicity:

LC50 Pimephales promelas (fathead minnow): 161 mg/L/96h.

12.2. Persistence and degradability

Further details:

Information about 2-Methoxy-1-methylethyl acetate:

Biodegradation:

100 %/8 d (OECD 302 B).

57.4 %/20 d (closed bottle test).

Information about 1,4-Dioxane:

Biodegradation: < 5 %/28 d (OECD 301 E).

Product is biodegradable with difficulty.

12.3 Bioaccumulative potential

Bioconcentration factor (BCF):

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

no data available

12.6 Other adverse effects

General information:

Do not allow to enter into ground-water, surface water or drains.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 10 of 12

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 16 03 05* = Organic wastes containing dangerous substances

* = Evidence for disposal must be provided.

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle empty containers with care. Incineration may cause explosion. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA: UN 1993

14.2 UN proper shipping name

ADR/RID, IMDG, IATA: UN 1993, FLAMMABLE LIQUID, N.O.S.(Dioxane, 2-Methoxy-1-methylethyl acetate solution)

14.3 Transport hazard class(es)

ADR/RID: Class 3, Code: F1

IMDG: Class 3, Subrisk -

IATA: Class 3

14.4 Packing group

ADR/RID, IMDG, IATA: III



14.5 Environmental hazards

Marine pollutant: No

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: ADR/RID: Kemmler-number 30, UN number 1993

Hazard label: 3

Special provisions: 274 601 640E

Limited quantities: 5 L

EQ: E1

Contaminated packaging - Instructions: P001 - IBC03 - LP01 - R001

Special provisions for packing together: MP19

Portable tanks - Instructions: T4

Portable tanks - Special provisions: TP1 TP29

Tank coding: LGBF

Tunnel restriction code: D/E

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 11 of 12

Sea transport (IMDG)

EmS: F-E, S-E
Special provisions: 223, 274, 955
Limited quantities: 5 L
EQ: E1
Contaminated packaging - Instructions: P001, LP01
Contaminated packaging - Provisions: -
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T4
Tank instructions - Provisions: TP1, TP29
Stowage and handling: Category A.
Properties and observations: -

Air transport (IATA)

Hazard: Flammable liquid
EQ: E1
Passenger Ltd.Qty.: Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L
Passenger: Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L
Cargo: Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L
Special Provisioning: A3
ERG: 3L

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

no data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

Hazchem-Code: •3Y

National regulations - EC member states

Volatile organic compounds (VOC):
approx. 70 % by weight = 700 g/L

Labelling of packaging with <= 125mL content



Signal word:

Warning

Hazard statements: H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
EUH019 May form explosive peroxides.
EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P201 Obtain special instructions before use.
P261 Avoid breathing vapours.
P312 Call a POISON CENTER/doctor if you feel unwell.
P405 Store locked up.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No 2015/830



Negative Photoresist AR-N 4240

Revision date: 24/2/2016

Version: 5

Language: en-GB,IE

Date of print: 24/2/2016

Page: 12 of 12

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Further information

Wording of the H-phrases under paragraph 2 and 3:

H225 = Highly flammable liquid and vapour.

H226 = Flammable liquid and vapour.

H301 = Toxic if swallowed.

H311 = Toxic in contact with skin.

H314 = Causes severe skin burns and eye damage.

H319 = Causes serious eye irritation.

H335 = May cause respiratory irritation.

H351 = Suspected of causing cancer.

H412 = Harmful to aquatic life with long lasting effects.

EUH019 = May form explosive peroxides.

EUH066 = Repeated exposure may cause skin dryness or cracking.

Reason of change: General revision (Regulation (EU) Nr. 2015/830)

Date of first version: 18/1/2011

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.