



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 17/1/2018  
Version: 11  
Language: en-GB,IE  
Date of print: 15/11/2018

## Positive Photoresist AR-P 3540, 3740, 3840 series

Material number AR-P 3540, 3740, 3840 series

Page: 1 of 11

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: Positive Photoresist AR-P 3540, 3740, 3840 series

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Intermediate for electronic industry

#### 1.3 Details of the supplier of the safety data sheet

Company name: Allresist  
Gesellschaft für chemische Produkte zur Mikrostrukturierung mbH  
Street/POB-No.: Am Biotop 14  
Postal Code, city: DE-15344 Strausberg  
WWW: [www.allresist.de](http://www.allresist.de)  
E-mail: [info@allresist.de](mailto:info@allresist.de)  
Telephone: +49 (0)33 41-35 93-0  
Telefax: +49 (0)33 41-35 93-29  
Dept. responsible for information:  
Frau Feldt, Email: [doerte.feldt@allresist.de](mailto:doerte.feldt@allresist.de)

#### 1.4 Emergency telephone number

Telephone: +49 (0)33 41-35 93-0  
Only available during office hours.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to EC regulation 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

Skin Irrit. 2; H315 Causes skin irritation.

Eye Irrit. 2; H319 Causes serious eye irritation.

#### 2.2 Label elements

##### Labelling (CLP)



Signal word:

**Warning**

Hazard statements: H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 17/1/2018

Version: 11

Language: en-GB,IE

Date of print: 15/11/2018

## Positive Photoresist AR-P 3540, 3740, 3840 series

Material number AR-P 3540, 3740, 3840 series

Page: 2 of 11

Precautionary statements: P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P235	Store in a well-ventilated place. Keep cool.

### Special labelling

Text for labelling: Contains 2-Methoxy-1-methylethyl acetate.

### 2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.  
Inhaling can lead to irritations of the respiratory tract and mucous membrane.  
Higher doses may lead to a narcotic effect.  
Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment:

No data available

## SECTION 3: Composition / information on ingredients

3.1 Substances: not applicable

### 3.2 Mixtures

Chemical characterisation: Mixture of the substances listed below with non-hazardous additions:

Hazardous ingredients:

Ingredient	Designation	Content	Classification
REACH 01-2119475791-29-xxxx EC No. 203-603-9 CAS 108-65-6	2-Methoxy-1-methylethyl acetate	50 - 75 %	Flam. Liq. 3; H226.
EC No. 270-931-7 CAS 68510-93-0	Naphthoquinone diazide	5 - 15 %	Flam. Sol. 2; H228. Self-react. CD; H242. Skin Irrit. 2; H315. Eye Irrit. 2; H319. Aquatic Chronic 3; H412.
EC No. 214-540-1 CAS 1143-72-2	2,3,4-trihydroxybenzophenone	< 2 %	Skin Irrit. 2; H315. Eye Irrit. 2; H319. STOT SE 3; H335.
EC No. 215-293-2 CAS 1319-77-3	Cresol-isomeric mixture	< 0.25 %	Acute Tox. 3; H301. Acute Tox. 3; H311. Skin Corr. 1B; H314.

Full text of H- and EUH-statements: see section 16.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 17/1/2018

Version: 11

Language: en-GB,IE

Date of print: 15/11/2018

## Positive Photoresist AR-P 3540, 3740, 3840 series

Material number AR-P 3540, 3740, 3840 series

Page: 3 of 11

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General information: IF exposed or concerned: Get medical advice/attention.  
If medical advice is needed, have product container or label at hand. First aider: Pay attention to self-protection!
- In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical aid in case of troubles.
- Following skin contact: Change contaminated clothing. Remove residues with soap and water. In case of skin irritation, consult a physician.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
- After swallowing: Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person.  
Do not induce vomiting. Seek medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye irritation.  
Inhaling can lead to irritations of the respiratory tract and mucous membrane.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media:  
Extinguishing powder, water spray jet or carbon dioxide.  
In case of large fires alcohol resistant foam or water spray jet.

- Extinguishing media which must not be used for safety reasons:  
Full water jet.

#### 5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour.  
With air, vapours form potentially explosive mixtures, which are heavier than air.  
Vapours may proceed on the ground over great distances and cause fire and backflashes.  
May form dangerous gases and vapours in case of fire.  
Furthermore, there may develop: nitrogen oxides, sulphur oxides, carbon monoxide and carbon dioxide.

#### 5.3 Advice for firefighters

- Special protective equipment for firefighters:  
Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

- Additional information: Hazchem-Code: •3Y  
Heating will lead to pressure increase: Danger of bursting and explosion. Keep containers cool with water spray.  
In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.  
Do not allow fire water to penetrate into surface or ground water.  
Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 17/1/2018

Version: 11

Language: en-GB,IE

Date of print: 15/11/2018

## Positive Photoresist AR-P 3540, 3740, 3840 series

Material number AR-P 3540, 3740, 3840 series

Page: 4 of 11

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol. Avoid contact with the substance. Ensure adequate ventilation, especially in confined areas.

Eliminate all ignition sources if safe to do so. If possible, eliminate leakage. Cordon off downwind area at risk and warn inhabitants. Solvent-resistant protective clothing recommended. Keep unprotected people away.

#### 6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion! In case of release, notify competent authorities.

#### 6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Beware of reignition. Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information: Use explosion-proof equipment and non-sparking tools/utensils.

Special danger of slipping by leaking/spilling product.

#### 6.4 Reference to other sections

Refer additionally to section 8 and 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe vapour/aerosol. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.

Avoid contact with skin, eyes, and clothing. Wear appropriate protective equipment.

Take off immediately all contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Wash hands thoroughly after handling.

Work place should be equipped with a shower and an eye rinsing apparatus.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Use grounding equipment. Use only explosion-protected equipment/instruments. Do not weld.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry. Keep only in the original container. Handle and open container with care.

Keep away from sources of ignition and heat. Protect from direct sunlight.

Store containers in upright position. Explosion protection required.

Qualified materials: steel, polypropylene.

Unsuitable materials: copper, zinc.

Storage temperature: 10 °C up to 18 °C.

Hints on joint storage:

Do not store together with strong oxidizing agents, acids or alkalis.

Keep away from food, drink and animal feedingstuffs.

#### 7.3 Specific end use(s)

No information available.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 17/1/2018  
Version: 11  
Language: en-GB,IE  
Date of print: 15/11/2018

## Positive Photoresist AR-P 3540, 3740, 3840 series

Material number AR-P 3540, 3740, 3840 series

Page: 5 of 11

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
108-65-6	2-Methoxy-1-methylethyl acetate	Europe: IOELV: STEL	550 mg/m <sup>3</sup> ; 100 ppm (may be absorbed through the skin)
		Europe: IOELV: TWA	275 mg/m <sup>3</sup> ; 50 ppm (may be absorbed through the skin)
		Great Britain: WEL-STEL	548 mg/m <sup>3</sup> ; 100 ppm (may be absorbed through the skin)
		Great Britain: WEL-TWA	274 mg/m <sup>3</sup> ; 50 ppm (may be absorbed through the skin)
		Ireland: 15 minutes	550 mg/m <sup>3</sup> ; 100 ppm (may be absorbed through the skin)
		Ireland: 8 hours	275 mg/m <sup>3</sup> ; 50 ppm (may be absorbed through the skin)
1319-77-3	Cresol-isomeric mixture	Europe: IOELV: TWA	22 mg/m <sup>3</sup> ; 5 ppm
		Ireland: 8 hours	22 mg/m <sup>3</sup> ; 5 ppm (may be absorbed through the skin)

#### 8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Explosion protection required.

#### Personal protection equipment

##### Occupational exposure controls

- Respiratory protection: When aerosols and vapours form: Use appropriate respiratory protection. Respiratory protection must be worn whenever the WEL levels have been exceeded. Use filter type A (= against vapours of organic substances) according to EN 14387.
- Hand protection: Protective gloves according to EN 374.  
Glove material: butyl caoutchouc (butyl rubber) - Layer thickness: 0.70 mm.  
Breakthrough time: > 480 min.  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Eye protection: Tightly sealed goggles according to EN 166.
- Body protection: Flame retardant, antistatic and chemical resistant protective clothing.
- General protection and hygiene measures: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour/aerosol. Do not get in eyes, on skin, or on clothing. Take off immediately all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink. Wash hands thoroughly after handling. Work place should be equipped with a shower and an eye rinsing apparatus.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

- Appearance: Physical state at 20 °C and 101.3 kPa: liquid  
Colour: brown red
- Odour: ester-like
- Odour threshold: No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 17/1/2018  
Version: 11  
Language: en-GB,IE  
Date of print: 15/11/2018

## Positive Photoresist AR-P 3540, 3740, 3840 series

Material number AR-P 3540, 3740, 3840 series

Page: 6 of 11

pH value:	No data available
Melting point/freezing point:	-66 °C (2-Methoxy-1-methylethyl acetate)
Initial boiling point and boiling range:	146 °C (2-Methoxy-1-methylethyl acetate)
Flash point/flash point range:	45.5 °C (2-Methoxy-1-methylethyl acetate)
Evaporation rate:	No data available
Flammability:	Flammable liquid and vapour.
Explosion limits:	No data available
Vapour pressure:	at 20 °C: 3.6 hPa (2-Methoxy-1-methylethyl acetate) at 50 °C: 21 hPa (2-Methoxy-1-methylethyl acetate)
Vapour density:	4.56
Density:	at 20 °C: approx. 1.1 g/mL
Water solubility:	at 20 °C: insoluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity, kinematic:	No data available
Explosive properties:	Vapours can form explosive mixtures with air.
Oxidizing characteristics:	No data available

### 9.2 Other information

Ignition temperature: 333 °C (2-Methoxy-1-methylethyl acetate)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Flammable liquid and vapour. Vapours can form explosive mixtures with air.

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

Heating will lead to pressure increase: Danger of bursting and explosion.

### 10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames.  
Protect against direct sunlight.

### 10.5 Incompatible materials

Strong oxidizing agents, acids, alkalis. Attacks many plastics and rubbers.

### 10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition: No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 17/1/2018

Version: 11

Language: en-GB,IE

Date of print: 15/11/2018

## Positive Photoresist AR-P 3540, 3740, 3840 series

Material number AR-P 3540, 3740, 3840 series

Page: 7 of 11

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.  
Acute toxicity (oral): Based on available data, the classification criteria are not met.  
ATEmix (calculated): ATE > 5000 mg/kg.  
Acute toxicity (dermal): Based on available data, the classification criteria are not met.  
ATEmix (calculated): 2000 mg/kg < ATE ≤ 5000 mg/kg.  
Acute toxicity (inhalative): Based on available data, the classification criteria are not met.  
ATEmix (calculated): ATE > 20 mg/L.  
Skin corrosion/irritation: Skin Irrit. 2; H315 = Causes skin irritation.  
Serious eye damage/irritation: Eye Irrit. 2; H319 = Causes serious eye irritation.  
Sensitisation to the respiratory tract: Lack of data.  
Skin sensitisation: Lack of data.  
Germ cell mutagenicity/Genotoxicity: Lack of data.  
Carcinogenicity: Lack of data.  
Reproductive toxicity: Lack of data.  
Effects on or via lactation: Lack of data.  
Specific target organ toxicity (single exposure): Lack of data.  
Specific target organ toxicity (repeated exposure): Lack of data.  
Aspiration hazard: Lack of data.

Other information: Information about 2-Methoxy-1-methylethyl acetate:  
LD50 Rat, oral: > 5000 mg/kg.  
LD50 Rabbit, dermal: > 2000 mg/kg.  
Information about Cresol-isomeric mixture:  
LD50 Rat, oral: 1454 mg/kg.  
LD50 Rabbit, dermal: 242 mg/kg.

#### Symptoms

In case of inhalation: Vapours > 100 ppm: irritant.  
If higher concentrations occur: strongly irritant.  
Other symptoms: depression of central nervous system, Cough and shortage of breath.  
Pulmonary edema is possible. Symptoms may occur with delay.  
In case of ingestion: May be harmful if swallowed.  
Other symptoms: Nausea, vomiting, depression of central nervous system.  
After contact with skin:  
Danger of cutaneous absorption. Prolonged/repetitive skin contact may cause skin defatting or dermatitis.  
After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 17/1/2018

Version: 11

Language: en-GB,IE

Date of print: 15/11/2018

## Positive Photoresist AR-P 3540, 3740, 3840 series

Material number AR-P 3540, 3740, 3840 series

Page: 8 of 11

### SECTION 12: Ecological information

#### 12.1 Toxicity

Aquatic toxicity: Information about 2-Methoxy-1-methylethyl acetate:  
Daphnia toxicity:  
EC50 Daphnia magna (Big water flea): > 500 mg/L/48h.  
Fish toxicity:  
LC50 Oncorhynchus mykiss: 134 mg/L/96h (OECD 203)  
Algae toxicity:  
EC50 Pseudokirchneriella subcapitata (green algae): > 1000 mg/L/96h  
Information about Naphthoquinone diazide:  
Fish toxicity:  
LC50 zebrafish 22 - 50 mg/L/96h.

#### 12.2 Persistence and degradability

Further details: Biodegradability:  
Information about 2-Methoxy-1-methylethyl acetate: 83 % /10 d (OECD 301 F).  
Easily bio-degradable  
Effects in sewage plants: Information about 2-Methoxy-1-methylethyl acetate:  
EC10 activated sludge: >1000 mg/L/30min (OECD 209)

#### 12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:  
No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

No data available

#### 12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Product

Waste key number: 16 03 05\* = Organic wastes containing hazardous substances  
\* = Evidence for disposal must be provided.

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.

##### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle empty containers with care. Incineration may cause explosion. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 17/1/2018

Version: 11

Language: en-GB,IE

Date of print: 15/11/2018

## Positive Photoresist AR-P 3540, 3740, 3840 series

Material number AR-P 3540, 3740, 3840 series

Page: 9 of 11

### SECTION 14: Transport information

#### 14.1 UN number

ADR/RID, IMDG, IATA-DGR:

UN 1993

#### 14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:

UN 1993, FLAMMABLE LIQUID, N.O.S. (2-Methoxy-1-methylethyl acetate)

#### 14.3 Transport hazard class(es)

ADR/RID:

Class 3, Code: F1

IMDG:

Class 3, Subrisk -

IATA-DGR:

Class 3



#### 14.4 Packing group

ADR/RID, IMDG, IATA-DGR:

III

#### 14.5 Environmental hazards

Marine pollutant:

no

#### 14.6 Special precautions for user

##### Land transport (ADR/RID)

Warning board:

ADR/RID: Kemmler-number 30, UN number UN 1993

Hazard label:

3

Special provisions:

274 601

Limited quantities:

5 L

EQ:

E1

Contaminated packaging - Instructions:

P001 IBC03 LP01 R001

Special provisions for packing together:

MP19

Portable tanks - Instructions:

T4

Portable tanks - Special provisions:

TP1 TP29

Tank coding:

LGBF

Tunnel restriction code:

D/E

##### Sea transport (IMDG)

EmS:

F-E, S-E

Special provisions:

223, 274, 955

Limited quantities:

5 L

Excepted quantities:

E1

Contaminated packaging - Instructions:

P001, LP01

Contaminated packaging - Provisions:

-

IBC - Instructions:

IBC03

IBC - Provisions:

-

Tank instructions - IMO:

-

Tank instructions - UN:

T4

Tank instructions - Provisions:

TP1, TP29

Stowage and handling:

Category A.

Properties and observations:

-

Segregation group:

none



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 17/1/2018  
Version: 11  
Language: en-GB,IE  
Date of print: 15/11/2018

## Positive Photoresist AR-P 3540, 3740, 3840 series

Material number AR-P 3540, 3740, 3840 series

Page: 10 of 11

### Air transport (IATA)

Hazard label:	Flamm. liquid
Excepted Quantity Code:	E1
Passenger and Cargo Aircraft: Ltd.Qty.:	Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L
Passenger and Cargo Aircraft:	Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L
Cargo Aircraft only:	Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L
Special provisions:	A3
Emergency Response Guide-Code (ERG):	3L

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations - Great Britain

Hazchem-Code: •3Y  
No data available

#### National regulations - EC member states

Volatile organic compounds (VOC):  
approx. 65 % by weight = 715 g/L

#### Labelling of packaging with <= 125mL content



Signal word: **Warning**

Hazard statements: not applicable

Precautionary statements: P261 Avoid breathing vapours/spray.

### 15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

## SECTION 16: Other information

### Further information

Wording of the H-phrases under paragraph 2 and 3:

H226 = Flammable liquid and vapour.  
H228 = Flammable solid.  
H242 = Heating may cause a fire.  
H301 = Toxic if swallowed.  
H311 = Toxic in contact with skin.  
H314 = Causes severe skin burns and eye damage.  
H315 = Causes skin irritation.  
H319 = Causes serious eye irritation.  
H335 = May cause respiratory irritation.  
H412 = Harmful to aquatic life with long lasting effects.

Reason of change: Changes in section 2: Labelling (P-phrases: EU, ATP 8)

Date of first version: 24/11/2010

### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 17/1/2018

Version: 11

Language: en-GB,IE

Date of print: 15/11/2018

## Positive Photoresist AR-P 3540, 3740, 3840 series

Material number AR-P 3540, 3740, 3840 series

Page: 11 of 11

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

