

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



Negative Photoresist SX AR-N 8520-01/1

Material number SX AR-N 8520-01/1

Revision date: 17/1/2018
Version: 2

Language: en-GB,IE

Date of print: 31/1/2018
Page: 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Negative Photoresist SX AR-N 8520-01/1

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Intermediate for electronic industry

1.3 Details of the supplier of the safety data sheet

Company name: Allresist
Gesellschaft für chemische Produkte zur Mikrostrukturierung mbH
Street/POB-No.: Am Biotop 14
Postal Code, city: 15344 Strausberg
Germany
WWW: www.allresist.de
E-mail: info@allresist.de
Telephone: +49 (0)33 41-35 93-0
Telefax: +49 (0)33 41-35 93-29
Dept. responsible for information:
Frau Feldt, Email: doerte.feldt@allresist.de

1.4 Emergency telephone number

Telephone: +49 (0)33 41-35 93-0
Only available during office hours.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.
Skin Irrit. 2; H315 Causes skin irritation.
Eye Irrit. 2; H319 Causes serious eye irritation.
STOT SE 3; H335 May cause respiratory irritation.
Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (CLP)



Signal word:

Warning

Hazard statements: H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



Negative Photoresist SX AR-N 8520-01/1

Material number SX AR-N 8520-01/1

Revision date: 17/1/2018
Version: 2

Language: en-GB,IE

Date of print: 31/1/2018
Page: 2 of 11

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Special labelling

Text for labelling: Contains Poly[(o-cresyl glycidyl ether)-co-formaldehyde].

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.
Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition / information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Mixture of the substances listed below with non-hazardous additions

Hazardous ingredients:

Ingredient	Designation	Content	Classification
REACH 01-2119475791-29-xxxx EC No. 203-603-9 CAS 108-65-6	2-Methoxy-1-methylethyl acetate	< 60 %	Flam. Liq. 3; H226.
EC No. - CAS 29690-82-2	Poly[(o-cresyl glycidyl ether)-co-formaldehyde]	>= 30 %	Skin Irrit. 2; H315. Eye Irrit. 2; H319. STOT SE 3; H335.
CAS 109037-75-4	Triarylsulfonium hexafluoroantimonate salts, mixed	< 5 %	Acute Tox. 4; H302. Acute Tox. 4; H332. Aquatic Chronic 2; H411.
REACH 01-2119537232-48-xxxx EC No. 203-572-1 CAS 108-32-7	Propylene carbonate	< 5 %	Eye Irrit. 2; H319.

Full text of H- and EUH-statements: see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



Negative Photoresist SX AR-N 8520-01/1

Material number SX AR-N 8520-01/1

Revision date: 17/1/2018
Version: 2

Language: en-GB,IE

Date of print: 31/1/2018
Page: 3 of 11

SECTION 4: First aid measures

4.1 Description of first aid measures

- General information: IF exposed or concerned: Get medical advice/attention.
If medical advice is needed, have product container or label at hand. First aider: Pay attention to self-protection!
- In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical aid in case of troubles.
- Following skin contact: Immediately clean with water and soap followed by thorough rinsing. Take off contaminated clothing.
In case of skin irritation, consult a physician.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
- After swallowing: Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person.
Do not induce vomiting. Immediately call a POISON CENTER/doctor.

4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye irritation.
May cause respiratory irritation. Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media:
Extinguishing powder, water fog or carbon dioxide.
In case of large fires alcohol resistant foam or water fog.
- Extinguishing media which must not be used for safety reasons:
Full water jet.

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour.
With air, vapours form potentially explosive mixtures, which are heavier than air.
Vapours may proceed on the ground over great distances and cause fire and backflashes.
May form dangerous gases and vapours in case of fire.
Furthermore, there may develop: sulphur oxides, carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

- Special protective equipment for firefighters:
Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



Negative Photoresist SX AR-N 8520-01/1

Material number SX AR-N 8520-01/1

Revision date: 17/1/2018

Version: 2

Language: en-GB,IE

Date of print: 31/1/2018

Page: 4 of 11

Additional information: Hazchem-Code: •3Y
Heating will lead to pressure increase: Danger of bursting and explosion. Keep containers cool with water spray.
In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Do not allow fire water to penetrate into surface or ground water.
Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol. Avoid contact with the substance. Take off contaminated clothing and wash it before reuse.
Ensure adequate ventilation, especially in confined areas.
Eliminate all ignition sources if safe to do so. If possible, eliminate leakage. Cordon off downwind area at risk and warn inhabitants.
Solvent-resistant protective clothing recommended. Keep unprotected people away.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion!
In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).
Beware of reignition. Thoroughly clean surrounding area.
In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information: Use explosion-proof equipment and non-sparking tools/utensils.
Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe vapour/aerosol. Take off contaminated clothing and wash it before reuse.
Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.
Avoid contact with skin, eyes, and clothing. Wear appropriate protective equipment. When using do not eat, drink or smoke. Wash hands thoroughly after handling. When handling large quantities, supply emergency spray.

Precautions against fire and explosion:
Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharge.
Use only explosion-protected equipment/instruments. Do not weld. In partially filled containers explosive mixtures may form.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



Negative Photoresist SX AR-N 8520-01/1

Material number SX AR-N 8520-01/1

Revision date: 17/1/2018
Version: 2

Language: en-GB,IE

Date of print: 31/1/2018
Page: 5 of 11

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place.
Keep container dry. Keep only in the original container. Handle and open container with care.
Keep away from sources of ignition and heat. Protect from direct sunlight.
Store containers in upright position. Explosion protection required.
Qualified materials: steel, polypropylene.
Unsuitable materials: Copper, zinc.
Storage temperature: 10 °C up to 22 °C.

Hints on joint storage: Do not store together with strong oxidizing agents, acids or alkalis.
Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
108-65-6	2-Methoxy-1-methylethyl acetate	Europe: IOELV: STEL	550 mg/m ³ ; 100 ppm (may be absorbed through the skin)
		Europe: IOELV: TWA	275 mg/m ³ ; 50 ppm (may be absorbed through the skin)
		Great Britain: WEL-STEL	548 mg/m ³ ; 100 ppm
		Great Britain: WEL-TWA	274 mg/m ³ ; 50 ppm
		Ireland: 15 minutes	550 mg/m ³ ; 100 ppm (may be absorbed through the skin)
		Ireland: 8 hours	275 mg/m ³ ; 50 ppm (may be absorbed through the skin)

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Explosion protection required.

Personal protection equipment Occupational exposure controls

Respiratory protection: When aerosols and vapours form: Use appropriate respiratory protection. Respiratory protection must be worn whenever the WEL levels have been exceeded. Use filter type A (= against vapours of organic substances) according to EN 14387.

Hand protection: Protective gloves according to EN 374.
Glove material: butyl caoutchouc (butyl rubber) - Layer thickness: 0.70 mm.
Breakthrough time: > 480 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to EN 166.

Body protection: Flame retardant, antistatic and chemical resistant protective clothing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



Negative Photoresist SX AR-N 8520-01/1

Material number SX AR-N 8520-01/1

Revision date: 17/1/2018
Version: 2

Language: en-GB,IE

Date of print: 31/1/2018
Page: 6 of 11

General protection and hygiene measures:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour/aerosol.
Do not get in eyes, on skin, or on clothing. Take off contaminated clothing and wash it before reuse.
When using do not eat or drink. Wash hands thoroughly after handling.
When handling large quantities, supply emergency spray.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Colour: colourless up to light yellow
Odour:	ester-like
Odour threshold:	No data available
pH value:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	146 °C (2-Methoxy-1-methylethyl acetate)
Flash point/flash point range:	45.5 °C (2-Methoxy-1-methylethyl acetate)
Evaporation rate:	No data available
Flammability:	Flammable liquid and vapour.
Explosion limits:	No data available
Vapour pressure:	at 20 °C: approx. 4 hPa (2-Methoxy-1-methylethyl acetate) at 50 °C: 21 hPa (2-Methoxy-1-methylethyl acetate)
Vapour density:	No data available
Density:	No data available
Solubility:	No data available
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity, kinematic:	No data available
Explosive properties:	Vapours can form explosive mixtures with air.
Oxidizing characteristics:	No data available

9.2 Other information

Ignition temperature: 333 °C (2-Methoxy-1-methylethyl acetate)

SECTION 10: Stability and reactivity

10.1 Reactivity

Flammable liquid and vapour. Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Heating will lead to pressure increase: Danger of bursting and explosion.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



Negative Photoresist SX AR-N 8520-01/1

Material number SX AR-N 8520-01/1

Revision date: 17/1/2018
Version: 2

Language: en-GB,IE

Date of print: 31/1/2018
Page: 7 of 11

10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames.
Protect against direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents, acids, alkalis. Attacks many plastics and rubbers.

10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition: No data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
Acute toxicity (oral): Based on available data, the classification criteria are not met.
ATEmix (calculated): 2000 mg/kg < ATE ≤ 5000 mg/kg.
Acute toxicity (dermal): Based on available data, the classification criteria are not met.
ATEmix (calculated): 2000 mg/kg < ATE ≤ 5000 mg/kg.
Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
ATEmix (calculated): ATE > 20 mg/L.
Skin corrosion/irritation: Skin Irrit. 2; H315 = Causes skin irritation.
Serious eye damage/irritation: Eye Irrit. 2; H319 = Causes serious eye irritation.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Lack of data.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): STOT SE 3; H335 = May cause respiratory irritation.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

Other information: Information about 2-Methoxy-1-methylethyl acetate:
LD50 Rat, oral: > 5000 mg/kg.
LD50 Rabbit, dermal: > 2000 mg/kg.
Information about Propylene carbonate:
LD50 Rat, oral: > 5000 mg/kg
LD50 Rabbit, dermal > 2000 mg/kg

Symptoms

After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



Negative Photoresist SX AR-N 8520-01/1

Material number SX AR-N 8520-01/1

Revision date: 17/1/2018
Version: 2

Language: en-GB,IE

Date of print: 31/1/2018
Page: 8 of 11

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.
Information about 2-Methoxy-1-methylethyl acetate:
Daphnia toxicity:
EC50 Daphnia magna (Big water flea): > 500 mg/L/48h.
Fish toxicity:
LC50 Oncorhynchus mykiss: 134 mg/L/96h (OECD 203)
Algae toxicity:
EC50 Pseudokirchneriella subcapitata (green algae): > 1000 mg/L/96h
Information about Propylene carbonate:
Daphnia toxicity:
EC50/LC50 Daphnia magna (Big water flea): >1000 mg/L/48h (OECD 202)
Fish toxicity:
LC50 Cyprinus carpio (Common Carp): >1000 mg/L/96h (EU Method C.1)
Algae toxicity:
EC50/LC50 Desmodesmus subspicatus (green algae): >900 mg/L/72h (OECD 201)
NOEC Desmodesmus subspicatus (green algae): 900 mg/L/72h (OECD 201)

12.2 Persistence and degradability

Further details: Biodegradability:
Information about 2-Methoxy-1-methylethyl acetate: 83 % /10 d (OECD 301 F). Easily bio-degradable
Information about Propylene carbonate: > 83%/28d (OECD 301B). Easily bio-degradable
Effects in sewage plants: Information about 2-Methoxy-1-methylethyl acetate:
EC10 activated sludge: >1000 mg/L/30min (OECD 209)

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:
No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 16 03 05* = Organic wastes containing hazardous substances
* = Evidence for disposal must be provided.

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



Negative Photoresist SX AR-N 8520-01/1

Material number SX AR-N 8520-01/1

Revision date: 17/1/2018
Version: 2

Language: en-GB,IE

Date of print: 31/1/2018
Page: 9 of 11

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle empty containers with care. Incineration may cause explosion. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA-DGR:
UN 1993

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:
UN 1993, FLAMMABLE LIQUID, N.O.S. (2-Methoxy-1-methylethyl acetate)

14.3 Transport hazard class(es)

ADR/RID: Class 3, Code: F1
IMDG: Class 3, Subrisk -
IATA-DGR: Class 3



14.4 Packing group

ADR/RID, IMDG, IATA-DGR:
III

14.5 Environmental hazards

Marine pollutant: no

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: ADR/RID: Kemmler-number 30, UN number UN 1993
Hazard label: 3
Special provisions: 274 601
Limited quantities: 5 L
EQ: E1
Contaminated packaging - Instructions: P001 IBC03 LP01 R001
Special provisions for packing together: MP19
Portable tanks - Instructions: T4
Portable tanks - Special provisions: TP1 TP29
Tank coding: LGBF
Tunnel restriction code: D/E

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



Negative Photoresist SX AR-N 8520-01/1

Material number SX AR-N 8520-01/1

Revision date: 17/1/2018
Version: 2

Language: en-GB,IE

Date of print: 31/1/2018
Page: 10 of 11

Sea transport (IMDG)

EmS: F-E, S-E
Special provisions: 223, 274, 955
Limited quantities: 5 L
Excepted quantities: E1
Contaminated packaging - Instructions: P001, LP01
Contaminated packaging - Provisions: -
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T4
Tank instructions - Provisions: TP1, TP29
Stowage and handling: Category A.
Properties and observations: -
Segregation group: none

Air transport (IATA)

Hazard label: Flamm. liquid
Excepted Quantity Code: E1
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L
Passenger and Cargo Aircraft: Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L
Cargo Aircraft only: Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L
Special provisions: A3
Emergency Response Guide-Code (ERG): 3L

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

Hazchem-Code: •3Y
No data available

National regulations - EC member states

Volatile organic compounds (VOC):
approx. 45 % by weight

Labelling of packaging with <= 125mL content



Signal word: **Warning**

Hazard statements: H412 Harmful to aquatic life with long lasting effects.
Precautionary statements: not applicable

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



Negative Photoresist SX AR-N 8520-01/1

Material number SX AR-N 8520-01/1

Revision date: 17/1/2018
Version: 2

Language: en-GB,IE

Date of print: 31/1/2018
Page: 11 of 11

SECTION 16: Other information

Further information

Wording of the H-phrases under paragraph 2 and 3:

- H226 = Flammable liquid and vapour.
- H302 = Harmful if swallowed.
- H315 = Causes skin irritation.
- H319 = Causes serious eye irritation.
- H332 = Harmful if inhaled.
- H335 = May cause respiratory irritation.
- H411 = Toxic to aquatic life with long lasting effects.
- H412 = Harmful to aquatic life with long lasting effects.

Reason of change: Changes in section 2: Labelling (P-phrases: EU, ATP 8)
Date of first version: 18/5/2017

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

