



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 24/4/2020

Version: 3

Language: en-GB,IE

Date of print: 27/8/2020

## Adhesion promotor AR 300-80 new

Material number AR 300-80 neu

Page: 1 of 11

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: Adhesion promotor AR 300-80 new

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Intermediate for electronic industry  
For industrial purposes only

#### 1.3 Details of the supplier of the safety data sheet

Company name: Allresist  
Gesellschaft für chemische Produkte zur Mikrostrukturierung mbH  
Street/POB-No.: Am Biotop 14  
Postal Code, city: 15344 Strausberg  
WWW: www.allresist.de  
E-mail: info@allresist.de  
Telephone: +49 (0)33 41-35 93-0  
Telefax: +49 (0)33 41-35 93-29  
Department responsible for information:  
Frau Dr. Zimmermann, Email: produktion@allresist.de

#### 1.4 Emergency telephone number

Telephone: +49 (0)33 41-35 93-0  
Only available during office hours.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

#### 2.2 Label elements

##### Labelling (CLP)



Signal word: **Warning**

Hazard statements: H226 Flammable liquid and vapour.

Precautionary Statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapours/spray.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P403+P235	Store in a well-ventilated place. Keep cool.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 24/4/2020

Version: 3

Language: en-GB,IE

Date of print: 27/8/2020

## Adhesion promotor AR 300-80 new

Material number AR 300-80 neu

Page: 2 of 11

### 2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.  
Inhaling can lead to irritations of the respiratory tract and mucous membrane.  
Higher doses may lead to a narcotic effect.  
Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment:

No data available

## SECTION 3: Composition / information on ingredients

3.1 Substances: not applicable

### 3.2 Mixtures

Hazardous ingredients:

Ingredient	Designation	Content	Classification
EC No. 203-603-9 CAS 108-65-6	2-Methoxy-1-methylethyl acetate	>= 90 %	Flam. Liq. 3; H226.
EC No. 229-929-1 CAS 6843-66-9	Dimethoxydiphenylsilane	< 5 %	Skin Irrit. 2; H315. Eye Irrit. 2; H319.

Full text of H- and EUH-statements: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General information:	IF exposed or concerned: Get medical advice/attention. First aider: Pay attention to self-protection!
In case of inhalation:	Move victim to fresh air; if necessary, provide artificial respiration or oxygen. If victim is at risk of losing consciousness, position and transport on their side. Seek medical attention.
Following skin contact:	Remove residues with soap and water. Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Immediately get medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

Inhaling can lead to irritations of the respiratory tract and mucous membrane.  
Higher doses may lead to a narcotic effect.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 24/4/2020

Version: 3

Language: en-GB,IE

Date of print: 27/8/2020

## Adhesion promotor AR 300-80 new

Material number AR 300-80 neu

Page: 3 of 11

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media:

Extinguishing powder, water spray jet or carbon dioxide.

In case of large fires: alcohol resistant foam or water spray jet.

Extinguishing media which must not be used for safety reasons:

Full water jet

#### 5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour. With air, vapours form potentially explosive mixtures, which are heavier than air. Vapours may proceed on the ground over great distances and cause fire and backflashes. In case of fire may be liberated: silicon dioxide, carbon monoxide and carbon dioxide.

#### 5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Hazchem-Code: •3Y

Heating will lead to pressure increase: Danger of bursting and explosion. Use fine water spray to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely. Do not allow fire water to penetrate into surface or ground water.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Do not breathe vapour/aerosol. Wear appropriate protective equipment. Keep unprotected people away. If possible, eliminate leakage. Cordon off downwind area at risk and warn inhabitants. Take off contaminated clothing and wash it before reuse.

#### 6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion! In case of release, notify competent authorities.

#### 6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Wash spill area with plenty of water. In case of spills of large quantities: Dam spills. Beware of reignition. Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

Special danger of slipping by leaking/spilling product.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 24/4/2020

Version: 3

Language: en-GB,IE

Date of print: 27/8/2020

## Adhesion promotor AR 300-80 new

Material number AR 300-80 neu

Page: 4 of 11

### 6.4 Reference to other sections

Refer additionally to section 8 and 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe vapour/aerosol. Take off contaminated clothing and wash it before reuse. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. When handling large quantities, supply emergency spray. Wear appropriate protective equipment. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Do not weld. In partially filled containers explosive mixtures may form.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place. Keep container dry. Keep only in the original container. Protect from heat and direct sunlight. Store containers in upright position. Explosion protection required. Avoid admission of air/oxygen (formation of peroxide).

Qualified materials: steel, polypropylene.

Unsuitable materials: copper, zinc.

Storage temperature: 10 °C up to 22 °C.

Hints on joint storage:

Do not store together with combustible or self-igniting materials or any highly flammable solids.

Do not store together with strong oxidizing agents. Keep away from food, drink and animal feedingstuffs.

### 7.3 Specific end use(s)

No information available.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 24/4/2020

Version: 3

Language: en-GB,IE

Date of print: 27/8/2020

## Adhesion promotor AR 300-80 new

Material number AR 300-80 neu

Page:

5 of 11

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
108-65-6	2-Methoxy-1-methylethyl acetate	Europe: IOELV: STEL	550 mg/m <sup>3</sup> ; 100 ppm (may be absorbed through the skin)
		Europe: IOELV: TWA	275 mg/m <sup>3</sup> ; 50 ppm (may be absorbed through the skin)
		Great Britain: WEL-STEL	548 mg/m <sup>3</sup> ; 100 ppm (may be absorbed through the skin)
		Great Britain: WEL-TWA	274 mg/m <sup>3</sup> ; 50 ppm (may be absorbed through the skin)
		Ireland: 15 minutes	550 mg/m <sup>3</sup> ; 100 ppm (may be absorbed through the skin)
		Ireland: 8 hours	275 mg/m <sup>3</sup> ; 50 ppm (may be absorbed through the skin)

#### 8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Explosion protection required.

#### Personal protection equipment

##### Occupational exposure controls

**Respiratory protection:** Respiratory protection must be worn whenever the WEL levels have been exceeded. Use filter type A (= against vapours of organic substances) according to EN 14387. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection:** Protective gloves according to EN 374.  
Glove material: Butyl caoutchouc (butyl rubber) - Layer thickness:  $\geq$  0.5 mm.  
Breakthrough time:  $\geq$  480 min.  
Unsuitable glove material:  
Protective gloves made of fabric, leather, natural rubber (NR), polychloroprene (CR), polyvinyl chloride (PVC), fluoro rubber (FKM), nitrile rubber (NBR).  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

**Eye protection:** Tightly sealed goggles according to EN 166.

**Body protection:** Flame retardant, antistatic and chemical resistant protective clothing.

**General protection and hygiene measures:**

Use only non-sparking tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Wash hands before breaks and after work. Do not breathe vapour/aerosol. When using do not eat, drink or smoke. Do not get in eyes, on skin, or on clothing. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. When handling large quantities, supply emergency spray.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 24/4/2020

Version: 3

Language: en-GB,IE

Date of print: 27/8/2020

## Adhesion promotor AR 300-80 new

Material number AR 300-80 neu

Page: 6 of 11

### Environmental exposure controls

Do not allow to enter into ground-water, surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Colour: colourless, clear
Odour:	ester-like
Odour threshold:	No data available
pH value:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	145 °C (2-Methoxy-1-methylethyl acetate)
Flash point/flash point range:	46 °C (2-Methoxy-1-methylethyl acetate)
Evaporation rate:	No data available
Flammability:	Flammable liquid and vapour.
Explosion limits:	LEL (Lower Explosion Limit): 1.50 Vol-% (2-Methoxy-1-methylethyl acetate) UEL (Upper Explosive Limit): 10.80 Vol-% (2-Methoxy-1-methylethyl acetate)
Vapour pressure:	at 20 °C: 3.1 hPa (2-Methoxy-1-methylethyl acetate)
Vapour density:	No data available
Density:	at 20 °C: approx. 1 g/mL
Solubility:	soluble (organic solvents)
Water solubility:	at 20 °C: 220 g/L (2-Methoxy-1-methylethyl acetate)
Partition coefficient: n-octanol/water:	1.2 log K(o/w) (2-Methoxy-1-methylethyl acetate) Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity, kinematic:	at 20 °C: 1.23 mm <sup>2</sup> /s (2-Methoxy-1-methylethyl acetate)
Explosive properties:	Vapours can form explosive mixtures with air.
Oxidizing characteristics:	No data available

### 9.2 Other information

Ignition temperature: 315 °C (2-Methoxy-1-methylethyl acetate)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Flammable liquid and vapour. Vapours can form explosive mixtures with air.

### 10.2 Chemical stability

Stable under recommended storage conditions.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 24/4/2020

Version: 3

Language: en-GB,IE

Date of print: 27/8/2020

## Adhesion promotor AR 300-80 new

Material number AR 300-80 neu

Page: 7 of 11

### 10.3 Possibility of hazardous reactions

Heating will lead to pressure increase: Danger of bursting and explosion.  
Reacts with strong oxidizing agents.  
Peroxide may form when product is exposed to light and air.

### 10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames.  
Protect from direct sunlight.

### 10.5 Incompatible materials

Strong oxidizing agents.

### 10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition: No data available

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.  
ATEmix calculated: > 5000 mg/kg

Acute toxicity (dermal): Based on available data, the classification criteria are not met.  
ATEmix calculated: > 2000 mg/kg

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.  
ATEmix calculated (Vapours): > 20 mg/L/4h

Skin corrosion/irritation: Lack of data.

Serious eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

Other information: Information about 2-Methoxy-1-methylethyl acetate:

LD50 Rat, oral: 8,500 mg/kg

LD50 Rabbit, dermal: > 2,000 mg/kg

LC50 Rat, inhalative (vapour): 35.7 mg/L/4h





# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 24/4/2020

Version: 3

Language: en-GB,IE

Date of print: 27/8/2020

## Adhesion promotor AR 300-80 new

Material number AR 300-80 neu

Page: 8 of 11

### SECTION 12: Ecological information

#### 12.1 Toxicity

Aquatic toxicity: Information about 2-Methoxy-1-methylethyl acetate:  
Daphnia toxicity:  
EC50 Daphnia magna (Big water flea): > 500 mg/L/48h  
NOEC Daphnia magna (Big water flea): >= 100 mg/L/21d (OECD 202)  
Fish toxicity:  
LC50 Oncorhynchus mykiss: 134 mg/L/96h (OECD 203)  
NOEC Oryzias latipes: 47.5 mg/L/14d (OECD 204)  
Algae toxicity:  
EC50 Selenastrum capricornutum: > 1000 mg/L/72h (OECD 201)

#### 12.2 Persistence and degradability

Further details: Information about 2-Methoxy-1-methylethyl acetate:  
Biodegradability: 83%/10 d (OECD 301 F). Easily bio-degradable

#### 12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:  
1.2 log K(o/w) (2-Methoxy-1-methylethyl acetate)  
Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

No data available

#### 12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Product

Waste key number: 07 01 04\* = Wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals.

\* = Evidence for disposal must be provided.

Recommendation: Dispose of waste according to applicable legislation.  
Do not dispose of with household waste.  
Do not empty into drains.

##### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.  
Handle empty containers with care. Incineration may cause explosion.  
Handle contaminated packages in the same way as the substance itself.





# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 24/4/2020  
Version: 3  
Language: en-GB,IE  
Date of print: 27/8/2020

## Adhesion promotor AR 300-80 new

Material number AR 300-80 neu

Page: 9 of 11

### SECTION 14: Transport information

#### 14.1 UN number

ADR/RID, IMDG, IATA-DGR:

UN 1993

#### 14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:

UN 1993, FLAMMABLE LIQUID, N.O.S. (2-Methoxy-1-methylethyl acetate)

#### 14.3 Transport hazard class(es)

ADR/RID:

Class 3, Code: F1

IMDG:

Class 3, Subrisk -

IATA-DGR:

Class 3



#### 14.4 Packing group

ADR/RID, IMDG, IATA-DGR:

III

#### 14.5 Environmental hazards

Marine pollutant:

no

#### 14.6 Special precautions for user

##### Land transport (ADR/RID)

Warning board:

ADR/RID: Kemmler-number 30, UN number UN 1993

Hazard label:

3

Special provisions:

274 601

Limited quantities:

5 L

EQ:

E1

Contaminated packaging - Instructions:

P001 IBC03 LP01 R001

Special provisions for packing together:

MP19

Portable tanks - Instructions:

T4

Portable tanks - Special provisions:

TP1 TP29

Tank coding:

LGBF

Tunnel restriction code:

D/E

##### Sea transport (IMDG)

EmS:

F-E, S-E

Special provisions:

223, 274, 955

Limited quantities:

5 L

Excepted quantities:

E1

Contaminated packaging - Instructions:

P001, LP01

Contaminated packaging - Provisions:

-

IBC - Instructions:

IBC03

IBC - Provisions:

-

Tank instructions - IMO:

-

Tank instructions - UN:

T4

Tank instructions - Provisions:

TP1, TP29

Stowage and handling:

Category A.

Properties and observations:

-

Segregation group:

none



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 24/4/2020  
Version: 3  
Language: en-GB,IE  
Date of print: 27/8/2020

## Adhesion promotor AR 300-80 new

Material number AR 300-80 neu

Page: 10 of 11

### Air transport (IATA)

Hazard label: Flamm. liquid  
Excepted Quantity Code: E1  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L  
Passenger and Cargo Aircraft: Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L  
Cargo Aircraft only: Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L  
Special provisions: A3  
Emergency Response Guide-Code (ERG): 3L

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations - Great Britain

Hazchem-Code: •3Y  
No data available

#### National regulations - EC member states

Volatile organic compounds (VOC):  
approx. 98 % by weight = 980 g/L

#### Labelling of packaging with <= 125mL content



Signal word: **Warning**

Hazard statements: not applicable

Precautionary Statements: P261 Avoid breathing vapours/spray.

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3, 40  
Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: P5c.

### 15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

## SECTION 16: Other information

### Further information

Wording of the H-phrases under paragraph 2 and 3:

H226 = Flammable liquid and vapour.  
H315 = Causes skin irritation.  
H319 = Causes serious eye irritation.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 24/4/2020

Version: 3

Language: en-GB,IE

Date of print: 27/8/2020

## Adhesion promotor AR 300-80 new

Material number AR 300-80 neu

Page: 11 of 11

### Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

AS/NZS: Australian Standards/New Zealand Standards

ATEmix: Acute Toxicity Estimate of mixture

CAS: Chemical Abstracts Service

CFR: Code of Federal Regulations

CLP: Classification, Labelling and Packaging

DMEL: Derived minimal effect level

DNEL: Derived no-effect level

EC50: Effective Concentration 50%

EC: European Community

EN: European Standard

EU: European Union

MFSU: Manufacture, formulation, supply and use

IATA: International Air Transport Association

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IMDG Code: International Maritime Dangerous Goods Code

LC50: Median lethal concentration

LD50: Lethal dose 50%

LEL: Lower Explosion Limit

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

NOEC: No Observed Effect Concentration

OECD: Organisation for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PBT: Persistent, bioaccumulative and toxic

PNEC: Predicted no-effect concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail

TLV: Threshold Limit Value

UN: United Nations

vPvB: Very persistent and very bioaccumulative

WEL: Workplace Exposure Limit

Reason of change: Changes in section 8: Occupational exposure limit values, biological limit values (Germany)  
Changes in section 15: Regulatory information  
General revision

Date of first version: 3/8/2018

### Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.