



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 16/4/2019

Version: 6

Language: en-GB,IE

Date of print: 28/8/2020

Positive E-Beam Resist SX AR-P 8100 Series

Material number SX AR-P 8100 Series

Page: 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Positive E-Beam Resist SX AR-P 8100 Series

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Intermediate for electronic industry

1.3 Details of the supplier of the safety data sheet

Company name: Allresist
Gesellschaft für chemische Produkte zur Mikrostrukturierung mbH
Street/POB-No.: Am Biotop 14
Postal Code, city: 15344 Strausberg
WWW: www.allresist.de
E-mail: info@allresist.de
Telephone: +49 (0)33 41-35 93-0
Telefax: +49 (0)33 41-35 93-29
Department responsible for information:
Frau Dr. Zimmermann, Email: produktion@allresist.de

1.4 Emergency telephone number

Telephone: +49 (0)33 41-35 93-0
Only available during office hours.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

2.2 Label elements

Labelling (CLP)



Signal word:

Warning

Hazard statements:

H226 Flammable liquid and vapour.

Precautionary Statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P403+P235 Store in a well-ventilated place. Keep cool.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 16/4/2019

Version: 6

Language: en-GB,IE

Date of print: 28/8/2020

Positive E-Beam Resist SX AR-P 8100 Series

Material number SX AR-P 8100 Series

Page: 2 of 11

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.

Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition / information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Hazardous ingredients:

Ingredient	Designation	Content	Classification
REACH 01-2119968918-13-xxxx EC No. 202-876-1 CAS 100-66-3	Anisole	>= 90 %	Flam. Liq. 3; H226.
CAS 25750-62-3	Polyphthalaldehyde	< 5 %	Skin Irrit. 2; H315. Eye Irrit. 2; H319. STOT SE 3; H335.
CAS 66003-78-9	Triphenylsulfonium triflate	< 5 %	Skin Irrit. 2; H315. Eye Irrit. 2; H319. STOT SE 3; H335.

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: If medical advice is needed, have product container or label at hand. First aider: Pay attention to self-protection!

In case of inhalation: Remove person to fresh air and keep comfortable for breathing. Seek medical treatment in case of troubles.

Following skin contact: Immediately clean with water and soap followed by thorough rinsing. Remove contaminated, saturated clothing. In case of skin reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.

After swallowing: Rinse mouth and drink large quantities of water. Never give anything by mouth to an unconscious person. Seek medical treatment in case of troubles.

4.2 Most important symptoms and effects, both acute and delayed

Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.

Cough, shortage of breath, nausea, vomiting, agitation, spasms, headache, tremors

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 16/4/2019

Version: 6

Language: en-GB,IE

Date of print: 28/8/2020

Positive E-Beam Resist SX AR-P 8100 Series

Material number SX AR-P 8100 Series

Page: 3 of 11

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet.

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour.

With air, vapours form potentially explosive mixtures, which are heavier than air. Vapours may proceed on the ground over great distances and cause fire and backflashes.

May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: sulphur oxides, hydrogen fluoride, carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Hazchem-Code: 3Y

Heating will lead to pressure increase: Danger of bursting and explosion. Keep containers cool with water spray.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol. Avoid contact with the substance. Ensure adequate ventilation, especially in confined areas.

Eliminate all ignition sources if safe to do so. If possible, eliminate leakage. Keep unprotected people away.

Wear appropriate protective equipment. Cordon off downwind area at risk and warn inhabitants.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion!

In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Beware of reignition. Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 16/4/2019

Version: 6

Language: en-GB,IE

Date of print: 28/8/2020

Positive E-Beam Resist SX AR-P 8100 Series

Material number SX AR-P 8100 Series

Page: 4 of 11

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe vapour/aerosol. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.

Avoid contact with skin, eyes, and clothing. Wear appropriate protective equipment.

When using do not eat, drink or smoke. Wash hands thoroughly after handling.

When handling large quantities, supply emergency spray.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Use grounding equipment.

Use only explosion-protected equipment/instruments. Do not weld.

In partially filled containers explosive mixtures may form.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry. Keep only in the original container. Protect from heat and direct sunlight.

Storage temperature: - 10 °C.

Hints on joint storage:

Do not store together with strong oxidizing agents, strong acids, alkalis or formaldehyde.

Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information: Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Explosion protection required.

Personal protection equipment

Occupational exposure controls

Respiratory protection:

When aerosols and vapours form: Use appropriate respiratory protection.

Use filter type A (= against vapours of organic substances) according to EN 14387.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 16/4/2019

Version: 6

Language: en-GB,IE

Date of print: 28/8/2020

Positive E-Beam Resist SX AR-P 8100 Series

Material number SX AR-P 8100 Series

Page: 5 of 11

Hand protection:	Protective gloves according to EN 374. Glove material: During full contact: Fluororubber (Viton) - Layer thickness: 0.70 mm. Breakthrough time: >480 min. During splash contact: Nitrile rubber - Layer thickness: 0.40 mm. Breakthrough time: >30 min. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Eye protection:	Tightly sealed goggles according to EN 166.
Body protection:	Flame retardant, antistatic and chemical resistant protective clothing.
General protection and hygiene measures:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour/aerosol. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink. Wash hands thoroughly after handling. When handling large quantities, supply emergency spray. Keep away from food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Colour: colourless up to light yellow
Odour:	aromatic
Odour threshold:	No data available
pH value:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	154 °C (Anisole)
Flash point/flash point range:	45.5 °C (Anisole)
Evaporation rate:	No data available
Flammability:	Flammable liquid and vapour.
Explosion limits:	LEL (Lower Explosion Limit): 0.34 Vol-% (Anisole) UEL (Upper Explosive Limit): 6.30 Vol-% (Anisole)
Vapour pressure:	at 20 °C: 3.2 - 32.0 hPa (Anisole)
Vapour density:	No data available
Density:	No data available
Solubility:	No data available
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	> 490 °C (Anisole)
Viscosity, kinematic:	No data available
Explosive properties:	Vapours can form explosive mixtures with air.
Oxidizing characteristics:	No data available

9.2 Other information

Ignition temperature:	475 °C (Anisole)
-----------------------	------------------



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 16/4/2019

Version: 6

Language: en-GB,IE

Date of print: 28/8/2020

Positive E-Beam Resist SX AR-P 8100 Series

Material number SX AR-P 8100 Series

Page: 6 of 11

SECTION 10: Stability and reactivity

10.1 Reactivity

Flammable liquid and vapour. Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Peroxide may form when product is exposed to light and air.

Heating will lead to pressure increase: Danger of bursting and explosion.

Violent reaction with strong oxidizing agents, strong acids, alkalis, formaldehyde.

10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames.

Protect from direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents, strong acids, alkalis, formaldehyde

10.6 Hazardous decomposition products

Peroxides

Thermal decomposition: > 490 °C (Anisole)



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 16/4/2019

Version: 6

Language: en-GB,IE

Date of print: 28/8/2020

Positive E-Beam Resist SX AR-P 8100 Series

Material number SX AR-P 8100 Series

Page: 7 of 11

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.
ATEmix (calculated): 2000 mg/kg < ATE <= 5000 mg/kg.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.
ATEmix (calculated): 2000 mg/kg < ATE <= 5000 mg/kg.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
ATEmix (calculated): ATE > 20 mg/L.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Information about Anisole:
Specific symptoms in animal studies (Rabbit): mild irritant (OECD404)

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Information about Anisole:
Specific symptoms in animal studies (Rabbit): Does not cause irritation. (OECD 405)

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Based on available data, the classification criteria are not met.

Information about Anisole:
Specific symptoms in animal studies (guinea pig): not sensitising (OECD 406)

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Information about Anisole:
Ames test Escherichia coli/Salmonella typhimurium: negative (OECD 471)
Gene-mutations mammalian cells, Mouse: negative (OECD 476)
Chromosomal aberrations mammalian cells, hamster: negative (OECD 473)

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

Other information: Information about Anisole:
LD50 Rat, oral: 3700 mg/kg
LC50 Rat, inhalative (vapours): > 6.51 mg/L/4h (OECD 403)



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 16/4/2019

Version: 6

Language: en-GB,IE

Date of print: 28/8/2020

Positive E-Beam Resist SX AR-P 8100 Series

Material number SX AR-P 8100 Series

Page: 8 of 11

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Information about Anisole:
Daphnia toxicity:
EC50 Daphnia magna (Big water flea): 27 mg/L/48h (OECD 202)
Fish toxicity:
LC50 Leuciscus idus: >1000 mg/L/96h
Algae toxicity:
ErC50 Selenastrum capricornutum: 47 mg/l/72h (OECD 201)

12.2 Persistence and degradability

Further details: Biodegradability:
Information about Anisole: approx. 68 % (OECD 301 D). Easily bio-degradable

Effects in sewage plants: Information about Anisole: NOEC activated sludge: 300 mg/L/3h (OECD 209)

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:
No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 07 01 04* = Organic solvents
* = Evidence for disposal must be provided.

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle empty containers with care. Incineration may cause explosion. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 16/4/2019

Version: 6

Language: en-GB,IE

Date of print: 28/8/2020

Positive E-Beam Resist SX AR-P 8100 Series

Material number SX AR-P 8100 Series

Page: 9 of 11

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA-DGR:

UN 2222

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:

UN 2222, ANISOLE mixture

14.3 Transport hazard class(es)

ADR/RID:

Class 3, Code: F1

IMDG:

Class 3, Subrisk -

IATA-DGR:

Class 3



14.4 Packing group

ADR/RID, IMDG, IATA-DGR:

III

14.5 Environmental hazards

Marine pollutant:

no

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board:

ADR/RID: Kemmler-number 30, UN number UN 2222

Hazard label:

3

Limited quantities:

5 L

EQ:

E1

Contaminated packaging - Instructions:

P001 IBC03 LP01 R001

Special provisions for packing together:

MP19

Portable tanks - Instructions:

T2

Portable tanks - Special provisions:

TP1

Tank coding:

LGBF

Tunnel restriction code:

D/E

Sea transport (IMDG)

EmS:

F-E, S-D

Special provisions:

-

Limited quantities:

5 L

Excepted quantities:

E1

Contaminated packaging - Instructions:

P001, LP01

Contaminated packaging - Provisions:

-

IBC - Instructions:

IBC03

IBC - Provisions:

-

Tank instructions - IMO:

-

Tank instructions - UN:

T2

Tank instructions - Provisions:

TP1

Stowage and handling:

Category A.

Properties and observations:

Colourless to yellow liquid. Flashpoint: 41°C c.c. Explosive limits: 0,3% to 6,3%. Immiscible with water. Irritating to skin, eyes and mucous membranes.

Segregation group:

none



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 16/4/2019
Version: 6
Language: en-GB,IE
Date of print: 28/8/2020

Positive E-Beam Resist SX AR-P 8100 Series

Material number SX AR-P 8100 Series

Page: 10 of 11

Air transport (IATA)

Hazard label: Flamm. liquid
Excepted Quantity Code: E1
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L
Passenger and Cargo Aircraft: Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L
Cargo Aircraft only: Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L
Emergency Response Guide-Code (ERG): 3L

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

Hazchem-Code: 3Y
No data available

National regulations - EC member states

Volatile organic compounds (VOC):
approx. 94 % by weight

Labelling of packaging with <= 125mL content



Signal word: **Warning**

Hazard statements: not applicable

Precautionary Statements:

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3, 40

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: P5c.

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Further information

Wording of the H-phrases under paragraph 2 and 3:

H226 = Flammable liquid and vapour.

H315 = Causes skin irritation.

H319 = Causes serious eye irritation.

H335 = May cause respiratory irritation.

EUH208 = Contains Phthalaldehyde. May produce an allergic reaction.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 16/4/2019

Version: 6

Language: en-GB,IE

Date of print: 28/8/2020

Positive E-Beam Resist SX AR-P 8100 Series

Material number SX AR-P 8100 Series

Page: 11 of 11

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

AS/NZS: Australian Standards/New Zealand Standards

CAS: Chemical Abstracts Service

CFR: Code of Federal Regulations

CLP: Classification, Labelling and Packaging

DMEL: Derived minimal effect level

DNEL: Derived no-effect level

EC50: Effective Concentration 50%

EC: European Community

EN: European Standard

EU: European Union

IATA: International Air Transport Association

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IMDG Code: International Maritime Dangerous Goods Code

LC50: Median lethal concentration

LD50: Lethal dose 50%

LEL: Lower Explosion Limit

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OSHA: Occupational Safety and Health Administration

PBT: Persistent, bioaccumulative and toxic

PNEC: Predicted no-effect concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail

STOT SE: Specific target organ toxicity - single exposure

UN: United Nations

vPvB: Very persistent and very bioaccumulative

Reason of change: Changes in section 15: Regulatory information

Date of first version: 18/5/2017

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.