ALLRESIST



Page 1/10

Revision: 12.12.2021

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: AR-N 2220

· Article number: AR-N 2220

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

 $No\ further\ relevant\ information\ available.$

· Application of the substance / the mixture

Intermediate product for the electronics industry. For industrial and commercial use only.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Allresist GmbH Am Biotop 14 15344 Strausberg GERMANY

E-Mail: info@allresist.de Tel.: +49 3341 35 93 0

- · Further information obtainable from: Sales
- · 1.4 Emergency telephone number: Poison center of the Charité Berlin:

+4930 30686700

E-Mail: giftnotruf@charite.de

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 12.12.2021 Version number 1.1 (replaces version 1.0) Revision: 12.12.2021

Trade name: AR-N 2220

(Contd. of page 1)

· Hazard pictograms





GHS02

· **Signal word** Danger

· Hazard-determining components of labelling:

butanone

2-methoxy-1-methylethyl acetate

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

L	· Dangerous components:		
Γ	CAS: 78-93-3		50-100%
	EINECS: 201-159-0	🔖 Flam. Liq. 2, H225; ၺ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
Γ		2-methoxy-1-methylethyl acetate	25-50%
	EINECS: 203-603-9	🚸 Flam. Liq. 3, H226; \psi STOT SE 3, H336	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After skin contact: Immediately rinse with water.

(Contd. on page 3)

Printing date 12.12.2021 Version number 1.1 (replaces version 1.0) Revision: 12.12.2021

Trade name: AR-N 2220

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Recommended storage temperature: 10-18°C
- · Storage class (TRGS): 3
- · 7.3 Specific end use(s) No further relevant information available.

GB

Version number 1.1 (replaces version 1.0) Printing date 12.12.2021 Revision: 12.12.2021

Trade name: AR-N 2220

(Contd. of page 3)

8.1 Contro	l parameters		
	's with limit values that requ	ire monitoring at th	ne workplace:
78-93-3 bi			
	t-term value: 899 mg/m³, 300		
	g-term value: 600 mg/m³, 200 BMGV) ppm	
	?-methoxy-1-methylethyl ace	etate	
	t-term value: 548 mg/m³, 10		
	g-term value: 274 mg/m³, 50		
Sk			
DNELs			
78-93-3 bu	ıtanone		
Oral	DNEL Long-term - oral, sys		31 mg/kg_bw/day (general public)
Dermal	DNEL Long-term – dermal,		1.161 mg/kg_bw/day (Worker)
	DNEL Acute - dermal, local		412 mg/kg (general public)
Inhalative	DNEL Long-term – inhalati	on, systemic effects	600 mg/m³/day (Worker)
			106 mg/m³/day (general public)
	?-methoxy-1-methylethyl ace		
Oral	DNEL Long-term - oral, systemic effects		1.67 mg/kg_bw/day (rat)
Dermal	DNEL Long-term – dermal, systemic effects		153.5 mg/kg_bw/day (rat)
Inhalative	DNEL long-term - inhalation local effects		$33 \text{ mg/m}^3 \text{ (rat)}$
	DNEL Long-term – inhalation, systemic effects		275 mg/m³/day (rat)
	DNEL Acute - inhalation, local effects		$2,420 \text{ mg/m}^3 \text{ (rat)}$
PNECs			
78-93-3 bu			
	rt term, fresh water	55.8 mg/l (Aquatic	
	rt term, sea water	55.8 mg/l (Aquatic	
	rt term, sewage plant	709 mg/l (Aquatic	,
	rt term fresh water sediment	284.7 mg/kg (Aqua	9
	rt term soil	22.5 mg/kg (teressi	,
	rt term, intermittent releases		organisms)
	?-methoxy-1-methylethyl ace		
	rt term, fresh water	0.635 mg/l (Aquatic organisms)	
	rt term, sea water	0.0635 mg/l (Aquatic organisms)	
	rt term, sewage plant	100 mg/l (Aquatic organisms)	
	rt term fresh water sediment	3.29 mg/kg (Aquatic organisms)	
PNEC short term soil PNEC short term sea water sediment		0.29 mg/kg (Aquatic organisms)	
	rt term sea water seatment rt term, intermittent releases	0.329 mg/kg (Aquatic organisms) 6.35 mg/l (Aquatic organisms)	
	·		organisms)
Ingredient 78-93-3 bi	's with biological limit value.	s:	
/ 8-93-3 b l BMGV 70			
	μmoi/L edium: urine		
	mpling time: post shift		

Printing date 12.12.2021 Version number 1.1 (replaces version 1.0) Revision: 12.12.2021

Trade name: AR-N 2220

(Contd. of page 4)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:
Fluid
Yellowish
Ester-like
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range 145 °C • Flammability Not applicable.

· Lower and upper explosion limit

· Lower: 1.5 Vol %
 · Upper: 10.8 Vol %
 · Flash point: 12 °C

(Contd. on page 6)

Printing date 12.12.2021 Version number 1.1 (replaces version 1.0) Revision: 12.12.2021

Trade name: AR-N 2220

(Contd. of page 5) Product is not selfigniting. · Auto-ignition temperature: Not determined. · Decomposition temperature: Mixture is non-soluble (in water). · Viscosity: Not determined. · Kinematic viscosity Not determined. · Dynamic: ·Solubility Fully miscible. · water: Partition coefficient n-octanol/water (log value) Not determined. 3.1 hPa · Vapour pressure at 20 °C: Density and/or relative density · Density at 20 °C: 1.04 g/cm^3 Not determined. · Relative density Not determined. · Vapour density · 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Ignition temperature: 315 °C Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. · Solvent content: · Organic solvents: 94.2-<94.3 % · VOC (EC) 94.24-<94.26 % · Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes Void · Explosives · Flammable gases Void Void · Aerosols · Oxidising gases Void · Gases under pressure Void· Flammable liquids Highly flammable liquid and vapour. · Flammable solids Void Void · Self-reactive substances and mixtures · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 7)

Printing date 12.12.2021 Version number 1.1 (replaces version 1.0) Revision: 12.12.2021

Trade name: AR-N 2220

(Contd. of page 6)

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC5	0 valu	es relevant for classification:
78-93-3	butana	one
Oral	LD50	3,300 mg/kg (rat)
Dermal	<i>LD50</i>	5,000 mg/kg (rabbit)
108-65-	6 2-me	thoxy-1-methylethyl acetate
Oral	LD50	8,532 mg/kg (rat)

- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

78-93-3 butanone

List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic to	xicity:	
78-93-3 bi	itanone	
Inhalative	LC50 (4h)	34.5 mg/l (rat)
	LC50 (96h) mg/ltr.	2,990 mg/ltr (Fish) (OECD 203)
	LC50 (48h) mg/ltr	>100 mg/ltr (Fish)
	EC50 (48h)	>100 mg/l (algae)
		>100 mg/l (Daphnia magna)
		308 mg/l (daphnia) (OECD 202)
	EC50 (72h)	1,972 mg/l (Pseudokirchneriella subcapitata)
	NOEC	1,150 mg/ml (Microorganism)
108-65-62	2-methoxy-1-methyl	ethyl acetate
Inhalative	LC50 (4h)	35.7 mg/l (rat)
	LC50 (96h) mg/ltr.	>100 mg/ltr (Fish)
		100-180 mg/ltr (Oncorhynchus mykiss)
		134 mg/ltr (rainbow trout)
	EC50 (48h)	408 mg/l (daphnia)
	ErC50 (96h)	>1,000 mg/ltr (algae)
	NOEC	100 mg/ml (daphnia)
· 12.2 Persi	stence and degradal	bility
78-93-3	butanone	98 %
108-65-6	2-methoxy-1-methyl	ethyl acetate 90 %
· Method		
108-65-6	2-methoxy-1-methyl	ethyl acetate 83
		(Contd. on page 8)

Printing date 12.12.2021 Version number 1.1 (replaces version 1.0) Revision: 12.12.2021

Trade name: AR-N 2220

(Contd. of page 7)

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN number or ID number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name ADR IMDG, IATA	1993 FLAMMABLE LIQUID, N.O.S. (ETHYL METHY KETONE (METHYL ETHYL KETONE), 2-methoxy-methylethyl acetate) FLAMMABLE LIQUID, N.O.S. (ETHYL METHY KETONE (METHYL ETHYL KETONE), 2-methoxy-methylethyl acetate)
ADR, IMDG, IATA Class Label	3 Flammable liquids.
	П
14.4 Packing group ADR, IMDG, IATA	II
	Not applicable.

Printing date 12.12.2021 Version number 1.1 (replaces version 1.0) Revision: 12.12.2021

Trade name: AR-N 2220

14.7 Maritime transport in bulk according	t o IMO Not applicable.
instruments	топ иррисионе.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (\widetilde{EQ})	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHY
3	METHYL KETONE (METHYL ETHYL KETONE),
	METHOXY-1-METHYLETHYL ACETATE), 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: (Substances not listed)

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · **VOC (EU)** 980.1-<980.3 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Disclaimer

This safety data sheet contains only safety relevant information. The information is based on the state of our knowledge at the time of revision, however, it does not constitute a guarantee of product properties, product information or product specifications and does not establish a contractual legal relationship. This document is only valid in its unchanged form. In the event of changes by third parties, the exhibitor accepts no responsibility for form and content or for any damages or claims arising from such changes. The information is not transferable to other products. If the product named in this safety data sheet is mixed, blended or processed with other materials or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise. The data sheet does not release the user from the obligation to ensure that he acts in accordance with all regulations in connection with his activity.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H319 Causes serious eye irritation.

(Contd. on page 10)

Printing date 12.12.2021 Version number 1.1 (replaces version 1.0) Revision: 12.12.2021

Trade name: AR-N 2220

(Contd. of page 9)

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: Quality Management department
- · Contact: MSDS authorized Person
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB