ALLRESIST



Safety data sheet according to 1907/2006/EC, Article 31 Page 1/10

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: <u>AR-P 1220</u>
- · Article number: AR-P 1220
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture
- Intermediate product for the electronics industry. For industrial and commercial use only.
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
- Allresist GmbH Am Biotop 14 15344 Strausberg GERMANY

E-Mail: info@allresist.de Tel.: +49 3341 35 93 0

- · Further information obtainable from: Sales
- 1.4 Emergency telephone number: Poison center of the Charité Berlin: +4930 30686700 E-Mail: giftnotruf@charite.de

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2H319 Causes serious eye irritation.STOT SE 3H336 May cause drowsiness or dizziness.

· 2.2 Label elements

• *Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.*

(Contd. on page 2)

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

		(Contd. of page
Hazard pictogr	ams	
1 Mr 1		
GHS02 GH	807	
011002 011		
Signal word Da	inger	
Hazard-determ	ining components of labelling:	
butanone		
	ethylethyl acetate	
Hazard stateme		
	ammable liquid and vapour.	
	erious eye irritation.	
	e drowsiness or dizziness.	
Precautionary :		
P101	If medical advice is needed, have product container or label at har	ıd.
P102	Keep out of reach of children.	
P103	Read carefully and follow all instructions.	
P210	Keep away from heat, hot surfaces, sparks, open flames and oth smoking.	er ignition sources.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.	
P280	Wear protective gloves/protective clothing/eye protection/fa protection.	ce protection/heari
P303+P361+P	353 IF ON SKIN (or hair): Take off immediately all contaminated ci	lothing. Rinse skin w
D204 D240	water [or shower].	1 .1 .
P304+P340	<i>IF INHALED: Remove person to fresh air and keep comfortable fo</i>	
r505+P551+P	338 IF IN EYES: Rinse cautiously with water for several minutes. Re present and easy to do. Continue rinsing.	emove contact lenses,
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional	l/national/internation
	regulations.	
Additional info	0	
	tains propyl 3,4,5-trihydroxybenzoate. May produce an allergic reactio	n.
2.3 Other hazar		

• **vPvB:** Not applicable.

Printing date 12.12.2021

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 78-93-3	butanone	50-100%
EINECS: 201-159-0	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
	2-methoxy-1-methylethyl acetate	≥25-≤50%
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	_
	propyl 3,4,5-trihydroxybenzoate	≥0.1-<0.25%
EINECS: 204-498-2	Eye Dam. 1, H318; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Sens. 1, H317	
		(Contd. on page

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Trade name: AR-P 1220

(Contd. of page 2)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After skin contact: Immediately rinse with water.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.

(Contd. on page 4)

GI

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

(Contd. of page 3)

Trade name: AR-P 1220

Store in cool, dry conditions in well sealed receptacles.

• Recommended storage temperature: 10-18°C

• Storage class (TRGS): 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1	Control parameters	
-----	---------------------------	--

	s with limit values that requ	ire monitoring at th	ne workplace:
78-93-3 bu			
Long	t-term value: 899 mg/m³, 300 g-term value: 600 mg/m³, 200 BMGV		
108-65-62	e-methoxy-1-methylethyl ace	etate	
	t-term value: 548 mg/m³, 10 g-term value: 274 mg/m³, 50		
DNELs			
78-93-3 bu	itanone		
Oral	DNEL Long-term - oral, sys	temic effects	31 mg/kg_bw/day (general public)
Dermal	DNEL Long-term – dermal,	systemic effects	1.161 mg/kg_bw/day (Worker)
	DNEL Acute - dermal, local	effects	412 mg/kg (general public)
Inhalative	DNEL Long-term – inhalati	on, systemic effects	600 mg/m³/day (Worker)
			106 mg/m³/day (general public)
108-65-62	-methoxy-1-methylethyl ace	etate	
Oral	DNEL Long-term - oral, sys	temic effects	1.67 mg/kg_bw/day (rat)
Dermal	DNEL Long-term – dermal,	systemic effects	153.5 mg/kg_bw/day (rat)
Inhalative	DNEL long-term - inhalatio	n local effects	33 mg/m ³ (rat)
	DNEL Long-term – inhalati	on, systemic effects	275 mg/m ³ /day (rat)
	DNEL Acute - inhalation, lo	ocal effects	2,420 mg/m ³ (rat)
PNECs			·
78-93-3 bu	itanone		
PNEC show	rt term, fresh water	55.8 mg/l (Aquatic	e organisms)
PNEC show	rt term, sea water	55.8 mg/l (Aquatic organisms)	
PNEC show	rt term, sewage plant	709 mg/l (Aquatic organisms)	
PNEC shot	rt term fresh water sediment	284.7 mg/kg (Aquatic organisms)	
PNEC show	rt term soil	22.5 mg/kg (teresstric organismens)	
PNEC short term, intermittent releases			
108-65-62	e-methoxy-1-methylethyl ace	etate	
PNEC sho	rt term, fresh water	0.635 mg/l (Aquat	ic organisms)
PNEC short term, sea water		0.0635 mg/l (Aquatic organisms)	
PNEC short term, sewage plant		100 mg/l (Aquatic organisms)	
PNEC show	rt term fresh water sediment	3.29 mg/kg (Aquat	tic organisms)
PNEC sho	rt term soil	0.29 mg/kg (Aquat	tic organisms)
DNEC ale	rt term sea water sediment	0.329 mg/kg (Aqua	atic organisms)
FILE SHOL		0 0 1	8

(Contd. on page 5)

⁻ GB

Printing date 12.12.2021

	(Contd. of page
Ingredie	ents with biological limit values:
78-93-3	butanone
BMGV	70 μmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one
Addition	nal information: The lists valid during the making were used as basis.
8.2 Exp	osure controls
Appropr	iate engineering controls No further data; see item 7.
	al protection measures, such as personal protective equipment
	protective and hygienic measures:
	ay from foodstuffs, beverages and feed.
	tely remove all soiled and contaminated clothing
	inds before breaks and at the end of work.
	ontact with the eyes.
	ontact with the eyes and skin.
	t ory protection: of brief exposure or low pollution use respiratory filter device. In case of intensive or longer expos
	contained respiratory protective device.
• Hand pr	
	Protective gloves we material has to be impermeable and resistant to the product/ the substance/ the preparation.
the chem	nissing tests no recommendation to the glove material can be given for the product/ the preparat nical mixture.
	n of the glove material on consideration of the penetration times, rates of diffusion and
degrada Mataria	tion I of gloves
The select and variant resistant application	ction of the suitable gloves does not only depend on the material, but also on further marks of qua ies from manufacturer to manufacturer. As the product is a preparation of several substances, ce of the glove material can not be calculated in advance and has therefore to be checked prior to
	ct break through time has to be found out by the manufacturer of the protective gloves and has to
	protection
	Tightly sealed goggles
	ON 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties General Information
- · Physical state
- · Colour:
- · Odour:
- · Odour threshold:

Fluid Brown Solvent-like Not determined.

(Contd. on page 6)

GB

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: AR-P 1220

	(Contd. of page
Melting point/freezing point:	-86 °C
Boiling point or initial boiling point and boiling	
range	79 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	-9 °C
Auto-ignition temperature:	Product is not selfigniting.
Decomposition temperature:	Not determined.
рН	Mixture is non-soluble (in water).
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
<i>Partition coefficient n-octanol/water (log value)</i>	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	1101 actor milliou.
Density analor relative density Density at 20 °C:	1 g/cm^3
Relative density	Not determined.
Kelalive aensily Vapour density	Not determined.
A V	1107 werer muteu.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and	!
environment, and on safety.	
Ignition temperature:	514 °C
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
Organic solvents:	97.3-<97.4 %
VÕC (EC)	97.28-<97.44 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	·
Explosives	Void
Explosives Flammable gases	Void
r tammable gases Aerosols	Void
	Void
Oxidising gases	
Gases under pressure	Void Uichle Gammable liquid and ear cun
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
	TT f
Pyrophoric liquids	Void
Pyrophoric liquids Pyrophoric solids	Void
Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures	
Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable	Void Void
Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable	Void
Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void
Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids	Void Void Void
Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids	Void Void Void Void
Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids	Void Void Void Void Void

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

(Contd. of page 6)

Trade name: AR-P 1220

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity

· LD/LC50 values relevant for classification:

78-93-3 butanone

Oral LD50 3,300 mg/kg (rat)

Dermal LD50 5,000 mg/kg (rabbit)

108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)

121-79-9 propyl 3,4,5-trihydroxybenzoate

Oral LD50 1,000-2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

• Serious eye damage/irritation Causes serious eye irritation.

• STOT-single exposure May cause drowsiness or dizziness.

• 11.2 Information on other hazards

· Endocrine disrupting properties

78-93-3 butanone

List II

SECTION 12: Ecological information

· 12.1 Toxicity

78-93-3 butanone			
Inhalative	LC50 (4h)	34.5 mg/l (rat)	
	LC50 (96h) mg/ltr.	2,990 mg/ltr (Fish) (OECD 203)	
	LC50 (48h) mg/ltr	>100 mg/ltr (Fish)	
	EC50 (48h)	>100 mg/l (algae)	
		>100 mg/l (Daphnia magna)	
		308 mg/l (daphnia) (OECD 202)	
	EC50 (72h)	1,972 mg/l (Pseudokirchneriella subcapitata)	
	NOEC	1,150 mg/ml (Microorganism)	
		1	(Contd. on page

GR

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: AR-P 1220

108-65-62	2-methoxy-1-methyl	ethyl acetate		(Contd. of page
	LC50 (4h)	35.7 mg/l (r		
	LC50 (96h) mg/ltr.	>100 mg/ltr	(Fish)	
		100-180 mg	/ltr (Oncorhynchus mykiss)	
		134 mg/ltr ((rainbow trout)	
	EC50 (48h)	408 mg/l (da	aphnia)	
	ErC50 (96h)	>1,000 mg/l	ltr (algae)	
	NOEC	100 mg/ml (daphnia)		
121-79-9 p	oropyl 3,4,5-trihydro	xybenzoate		
	EC50 (48h)	19.06 mg/l ((daphnia)	
	EC50 (3h)	636 mg/l (M	licroorganism)	
12.2 Persi	stence and degradal	oility		
78-93-3	butanone		98 %	
108-65-6	2-methoxy-1-methyle	ethyl acetate	90 %	
Method				
108-65-6	2-methoxy-1-methyle	ethyl acetate	83	
12.4 Mobi	c <mark>cumulative potentia</mark> lity in soil No furthe lts of PBT and vPvB	r relevant inf		

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

• 12.7 Other adverse effects No further relevant information available.

• Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

system.

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1993	
· 14.2 UN proper shipping name		
· ADR	1993 FLAMMABLE LIQUID, N.O.S. (ETHYL METHY	
	KETONE (METHYL ETHYL KETONE), 2-methoxy-	
	methylethyl acetate)	

[·] Recommendation

[·] Uncleaned packaging:

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: AR-P 1220

	(Contd. of page
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ETHYL METHY KETONE (METHYL ETHYL KETONE), 2-methoxy- methylethyl acetate)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E, <u>S-E</u> B
Stowage Category	
14.7 Maritime transport in bulk according to IM instruments	<i>IO</i> Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ)	1L.
Excepted quantities (EQ)	Code: E2
· · · · ·	Maximum net quantity per inner packaging: 30 ml
-	Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 D/E
IMDG Limited quantities (LQ)	11.
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHY METHYL KETONE (METHYL ETHYL KETONE), A METHOXY-1-METHYLETHYL ACETATE), 3, II

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: (Substances not listed)

None of the ingredients is listed.

• Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 10) GB

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: AR-P 1220

(Contd. of page 9)

- · National regulations:
- · VOC (EU) 972.8-<974.4 g/l
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Disclaimer

This safety data sheet contains only safety relevant information. The information is based on the state of our knowledge at the time of revision, however, it does not constitute a guarantee of product properties, product information or product specifications and does not establish a contractual legal relationship. This document is only valid in its unchanged form. In the event of changes by third parties, the exhibitor accepts no responsibility for form and content or for any damages or claims arising from such changes. The information is not transferable to other products. If the product named in this safety data sheet is mixed, blended or processed with other materials or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise. The data sheet does not release the user from the obligation to ensure that he acts in accordance with all regulations in connection with his activity.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- May cause an allergic skin reaction. H317
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H410 *Very toxic to aquatic life with long lasting effects.*
- EUH066 Repeated exposure may cause skin dryness or cracking.
- · Department issuing SDS: Quality Management department
- · Contact: MSDS authorized Person

· Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1