



Safety data sheet

Page 1/10

according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.0

Revision: 12.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: <u>AR-P 3500 T series</u>
- · Article number: AR-P 3510 T, AR-P 3540 T
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture
- Intermediate product for the electronics industry. For industrial and commercial use only.
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
- Allresist GmbH Am Biotop 14 15344 Strausberg GERMANY

E-Mail: info@allresist.de Tel.: +49 3341 35 93 0

- · Further information obtainable from: Sales
- 1.4 Emergency telephone number: Poison center of the Charité Berlin: +4930 30686700 E-Mail: giftnotruf@charite.de

SECTION 2: Hazards identification

- \cdot 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Eye Irrit. 2H319 Causes serious eye irritation.Skin Sens. 1H317 May cause an allergic skin reaction.STOT SE 3H336 May cause drowsiness or dizziness.Aquatic Chronic 3H412 Harmful to aquatic life with long lasting effects.• 2.2 Label elements• Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.0

Revision: 12.12.2021

Trade name: AR-P 3500 T series



• *PBT:* Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	<i>≥50-≤100%</i>
CAS: 68510-93-0 EINECS: 270-931-7	Naphthochinondiazid Flam. Sol. I, H228; Self-react. C, H242; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	≥2.5-<10%
	propyl 3,4,5-trihydroxybenzoate Eye Dam. 1, H318; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Sens. 1, H317	≥1-<2.5%
	()	Contd. on page 3)

Printing date 12.12.2021

Version number 1.0

Revision: 12.12.2021

Trade name: AR-P 3500 T series

	(Contd. of page 2)
CAS: 1143-72-2 2,3,4-trihydroxybenzophenone	≥0-<2.5%
EINECS: 214-540-1 🚯 Skin Irrit. 2, H315; STOT SE 3, H335; Aquatic Chronic 3, H412	
CAS: 1319-77-3 cresol (mix)	≥0-<1%
EINECS: 215-293-2 🚸 Acute Tox. 3, H301; Acute Tox. 3, H311; 🔣 Skin Corr. 1B, H314; Eye Dam. 1, H318	-

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- *General information: Immediately remove any clothing soiled by the product.*
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
 - *Ensure adequate ventilation.*
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 4)

Printing date 12.12.2021

Version number 1.0

Revision: 12.12.2021

Trade name: AR-P 3500 T series

(Contd. of page 3)

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

• 7.2 Conditions for safe storage, including any incompatibilities

• Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep container tightly sealed.

• Recommended storage temperature: 10-18°C

• Storage class (TRGS): 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

· DNELs

108-65-6 2-methoxy-1-methylethyl acetate

Oral	DNEL Long-term - oral, systemic effects	1.67 mg/kg_bw/day (rat)
Dermal	DNEL Long-term – dermal, systemic effects	153.5 mg/kg_bw/day (rat)
Inhalative	DNEL long-term - inhalation local effects	33 mg/m ³ (rat)
	DNEL Long-term – inhalation, systemic effects	275 mg/m³/day (rat)
	DNEL Acute - inhalation, local effects	2,420 mg/m ³ (rat)

· PNECs

108-65-6 2-methoxy-1-methylethyl acetate

PNEC short term, fresh water	0.635 mg/l (Aquatic organisms)
PNEC short term, sea water	0.0635 mg/l (Aquatic organisms)
PNEC short term, sewage plant	100 mg/l (Aquatic organisms)
PNEC short term fresh water sediment	3.29 mg/kg (Aquatic organisms)
PNEC short term soil	0.29 mg/kg (Aquatic organisms)
PNEC short term sea water sediment	0.329 mg/kg (Aquatic organisms)
PNEC short term, intermittent releases	6.35 mg/l (Aquatic organisms)

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Printing date 12.12.2021

Version number 1.0

Revision: 12.12.2021

Trade name: AR-P 3500 T series

(Contd. of page 4)

Avoid contact with the eyes. Avoid contact with the eyes and skin.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information Physical state	Fluid
Colour:	Brown
Odour:	Ester-like
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	l boiling
range	145 °C
Flammability	Not applicable.
Lower and upper explosion limit	**
Lower:	1.5 Vol %
Upper:	10.8 Vol %
Flash point:	46 °C
Auto-ignition temperature:	Product is not selfigniting.
Decomposition temperature:	Not determined.
pH	Mixture is non-soluble (in water).
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Fully miscible.

(Contd. on page 6)

GB

Printing date 12.12.2021

Version number 1.0

Revision: 12.12.2021

Trade name: AR-P 3500 T series

	(Contd. of page
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	3.1 hPa
Density and/or relative density	
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and	d
environment, and on safety.	
Ignition temperature:	315 °C
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Solvent content:	explosive an vapour mixtures are possible.
Organic solvents:	75.5-<84.3 %
VOC (EC)	75.52-<84.31 %
Change in condition	/ 5.52- <67.51 / 6
Evaporation rate	Not determined.
•	
Information with regard to physical hazard classe	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

GB

Printing date 12.12.2021

Version number 1.0

Revision: 12.12.2021

Trade name: AR-P 3500 T series

(Contd. of page 6)

SECTION 11: Toxicological information

 \cdot 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute	toxicity
---------	----------

· LD/LC50	· LD/LC50 values relevant for classification:		
ATE (Acu	ATE (Acute Toxicity Estimates)		
Oral	LD50 >54,258-108,767 mg/kg (rat)		
Dermal	LD50 > 565,931-626,959 mg/kg		
108-65-62	2-methoxy-1-methylethyl acetate		
Oral	LD50 8,532 mg/kg (rat)		
68510-93-	0 Naphthochinondiazid		
Oral	LD50 >5,000 mg/kg (rat)		
121-79-9	121-79-9 propyl 3,4,5-trihydroxybenzoate		
Oral	LD50 1,000-2,000 mg/kg (rat)		
Dermal	LD50 >2,000 mg/kg (rat)		
1319-77-3	cresol (mix)		
Oral	LD50 1,454 mg/kg (rat)		
Dermal	LD50 2,000 mg/kg (rabbit)		
Inhalative	LD50 1.21 mg/kg (rat)		
Respirator STOT-sin	 Serious eye damage/irritation Causes serious eye irritation. Respiratory or skin sensitisation May cause an allergic skin reaction. STOT-single exposure May cause drowsiness or dizziness. 11.2 Information on other hazards 		
· Endocrine	e disrupting properties		
None of th	None of the ingredients is listed.		

SECTION 12: Ecological information

Inhalative	LC50 (4h)	35.7 mg/l (rat)
	LC50 (96h) mg/ltr.	>100 mg/ltr (Fish)
		100-180 mg/ltr (Oncorhynchus mykiss)
		134 mg/ltr (rainbow trout)
	EC50 (48h)	408 mg/l (daphnia)
	ErC50 (96h)	>1,000 mg/ltr (algae)
	NOEC	100 mg/ml (daphnia)
121-79-9 р	bropyl 3,4,5-trihydro	pxybenzoate
	EC50 (48h)	19.06 mg/l (daphnia)
	EC50 (3h)	636 mg/l (Microorganism)
1319-77-3	cresol (mix)	
	LC50 (96) ppm	19 ppm (Fish)
12.2 Persis	stence and degradal	bility
108-65-6	2-methoxy-1-methyl	ethyl acetate 90 %

Printing date 12.12.2021

· Method

Version number 1.0

Revision: 12.12.2021

Trade name: AR-P 3500 T series

(Contd. of page 7)

- 108-65-6 2-methoxy-1-methylethyl acetate 83
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects No further relevant information available.
- **Remark:** Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN number or ID number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name ADR	1993 FLAMMABLE LIQUID, N.O.S. (2-methoxy-1 methylethyl acetate)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (2-methoxy-1 methylethyl acetate)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids. 30

Printing date 12.12.2021

Version number 1.0

Revision: 12.12.2021

Trade name: AR-P 3500 T series

	(Contd. of page
EMS Number:	F-E,S-E
· Stowage Category	A
14.7 Maritime transport in bulk according	g to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: El
· · · · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (2-METHOX)
	1-METHYLETHYL ACETATE), 3, III

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: (Substances not listed)

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

• VOC (EU) 755.2-<843.1 g/l

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Disclaimer

This safety data sheet contains only safety relevant information. The information is based on the state of our knowledge at the time of revision, however, it does not constitute a guarantee of product properties, product information or product specifications and does not establish a contractual legal relationship. This document is only valid in its unchanged form. In the event of changes by third parties, the exhibitor accepts no responsibility for form and content or for any damages or claims arising from such changes. The information is not transferable to other products. If the product named in this safety data sheet is mixed, blended or processed with other materials or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise. The data sheet does not release the user from the obligation to ensure that he acts in accordance with all regulations in connection with his activity.

· Relevant phrases

H226 Flammable liquid and vapour. H228 Flammable solid.

(Contd. on page 10)

GB

Printing date 12.12.2021

Version number 1.0

Revision: 12.12.2021

Trade name: AR-P 3500 T series

	(Contd. of page 9)
H242 Heating may cause a fire.	
H301 Toxic if swallowed.	
H302 Harmful if swallowed.	
H311 Toxic in contact with skin.	
H314 Causes severe skin burns and eye damage.	
H315 Causes severe skin burns and eye damage. H315 Causes skin irritation.	
H317 May cause an allergic skin reaction.	
H318 Causes serious eye damage.	
H319 Causes serious eye irritation.	
H335 May cause respiratory irritation.	
H336 May cause drowsiness or dizziness.	
H410 Very toxic to aquatic life with long lasting effects.	
H412 Harmful to aquatic life with long lasting effects.	
• Department issuing SDS: Quality Management department	
• Contact: MSDS authorized Person	
· Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par route (Europ	pean Agreement Concerning the
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)	
PNEC: Predicted No-Effect Concentration (REACH)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Flam. Sol. 1: Flammable solids – Category 1	
Self-react. C: Self-reactive substances and mixtures – Type C/D	
Acute Tox. 3: Acute toxicity – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Imit 2: Skin corrosion/irritation – Category 2	
Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Dam. 1. Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Skin Sens. 1: Skin sensitisation – Category 1	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
	GB