



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *SX AR-P 3500/8*
- **Article number:** *SX AR-P 3500/8*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Intermediate product for the electronics industry. For industrial and commercial use only.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Allresist GmbH
Am Biotop 14
15344 Strausberg
GERMANY*

- *E-Mail: info@allresist.de
Tel.: +49 3341 35 93 0*
- **Further information obtainable from:** *Sales*
- **1.4 Emergency telephone number:**
*Poison center of the Charité Berlin:
+4930 30686700
E-Mail: giftnotruf@charite.de*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

*flame**Flam. Liq. 3 H226 Flammable liquid and vapour.**Skin Irrit. 2 H315 Causes skin irritation.**Skin Sens. 1 H317 May cause an allergic skin reaction.**STOT SE 3 H336 May cause drowsiness or dizziness.*

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: SX AR-P 3500/8

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07

· Signal word *Warning*

· Hazard-determining components of labelling:

*2-methoxy-1-methylethyl acetate**bis[4-(2,3-epoxypropoxy)phenyl]propane*

· Hazard statements

*H226 Flammable liquid and vapour.**H315 Causes skin irritation.**H317 May cause an allergic skin reaction.**H336 May cause drowsiness or dizziness.*

· Precautionary statements

*P101 If medical advice is needed, have product container or label at hand.**P102 Keep out of reach of children.**P103 Read carefully and follow all instructions.**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**P241 Use explosion-proof [electrical/ventilating/lighting] equipment.**P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.**P321 Specific treatment (see on this label).**P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].**P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.**P362+P364 Take off contaminated clothing and wash it before reuse.**P405 Store locked up.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	50-100%
CAS: 68510-93-0 EINECS: 270-931-7	Naphthochinondiazid ⚠ Flam. Sol. 1, H228; Self-react. C, H242; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	≥2.5-<10%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: SX AR-P 3500/8

(Contd. of page 2)

CAS: 1143-72-2 EINECS: 214-540-1	2,3,4-trihydroxybenzophenone ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; Aquatic Chronic 3, H412	≥0-<2.5%
CAS: 1675-54-3 EINECS: 216-823-5	bis[4-(2,3-epoxypropoxy)phenyl]propane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	≥1-<2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: SX AR-P 3500/8

(Contd. of page 3)

Prevent formation of aerosols.

- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Keep container tightly sealed.

- **Recommended storage temperature:** 10-18°C

- **Storage class (TRGS):** 3

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
Sk	

- **DNELs**

108-65-6 2-methoxy-1-methylethyl acetate

Oral	DNEL Long-term - oral, systemic effects	1.67 mg/kg_bw/day (rat)
Dermal	DNEL Long-term - dermal, systemic effects	153.5 mg/kg_bw/day (rat)
Inhalative	DNEL long-term - inhalation local effects	33 mg/m ³ (rat)
	DNEL Long-term - inhalation, systemic effects	275 mg/m ³ /day (rat)
	DNEL Acute - inhalation, local effects	2,420 mg/m ³ (rat)

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Dermal	DNEL Long-term - dermal, systemic effects	8.33 mg/kg_bw/day (Worker)
	DNEL Acute - dermal systemic effects	8.33 mg/kg bw/day (Worker)
Inhalative	DNEL Long-term - inhalation, systemic effects	12.25 mg/m ³ /day (Worker)
	DNEL Acute inhalation systemic effects	12.25 mg/m ³ (Worker)

- **PNECs**

108-65-6 2-methoxy-1-methylethyl acetate

PNEC short term, fresh water	0.635 mg/l (Aquatic organisms)
PNEC short term, sea water	0.0635 mg/l (Aquatic organisms)
PNEC short term, sewage plant	100 mg/l (Aquatic organisms)
PNEC short term fresh water sediment	3.29 mg/kg (Aquatic organisms)
PNEC short term soil	0.29 mg/kg (Aquatic organisms)
PNEC short term sea water sediment	0.329 mg/kg (Aquatic organisms)
PNEC short term, intermittent releases	6.35 mg/l (Aquatic organisms)

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

PNEC short term, fresh water	0.006 mg/l (Aquatic organisms)
PNEC short term, sea water	0.001 mg/l (Aquatic organisms)
PNEC short term fresh water sediment	0.341 mg/kg (Aquatic organisms)
PNEC short term soil	0.065 mg/kg (Aquatic organisms)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: SX AR-P 3500/8

(Contd. of page 4)

PNEC short term sea water sediment	0.034 mg/kg (Aquatic organisms)
------------------------------------	---------------------------------

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

Red-brown

· **Odour:**

Ester-like

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

145 °C

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

1.5 Vol %

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: SX AR-P 3500/8

(Contd. of page 5)

· Upper:	10.8 Vol %
· Flash point:	44 °C
· Auto-ignition temperature:	Product is not selfigniting.
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	3.1 hPa
· Density and/or relative density	
· Density at 20 °C:	1.04 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	315 °C
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	73.4 %
· VOC (EC)	73.42 %
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: SX AR-P 3500/8

(Contd. of page 6)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
------	------	-------------------

68510-93-0 Naphthochinondiazid

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>2,000 mg/kg (rat)
--------	------	--------------------

- **Skin corrosion/irritation** Causes skin irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	List II
-----------	--	---------

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

108-65-6 2-methoxy-1-methylethyl acetate

Inhalative	LC50 (4h)	35.7 mg/l (rat)
	LC50 (96h) mg/ltr.	>100 mg/ltr (Fish)
		100-180 mg/ltr (Oncorhynchus mykiss)
		134 mg/ltr (rainbow trout)
	EC50 (48h)	408 mg/l (daphnia)
	ErC50 (96h)	>1,000 mg/ltr (algae)
NOEC	100 mg/ml (daphnia)	

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

LC50 (96h) mg/ltr.	1.5 mg/ltr (rainbow trout)
--------------------	----------------------------

- **12.2 Persistence and degradability**

108-65-6	2-methoxy-1-methylethyl acetate	90 %
1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	5 %

- **Method**

108-65-6	2-methoxy-1-methylethyl acetate	83
----------	---------------------------------	----

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: SX AR-P 3500/8


(Contd. of page 7)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA | <p style="text-align: center;">UN1993</p> |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA | <p style="text-align: center;">1993 FLAMMABLE LIQUID, N.O.S. (2-methoxy-1-methylethyl acetate)</p> <p style="text-align: center;">FLAMMABLE LIQUID, N.O.S. (2-methoxy-1-methylethyl acetate)</p> |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA | <div style="text-align: center;">  </div> <p style="text-align: center;">3 Flammable liquids.</p> <p style="text-align: center;">3</p> |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | <p style="text-align: center;">III</p> |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: | <p style="text-align: center;">Not applicable.</p> |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category | <p style="text-align: center;">Warning: Flammable liquids.</p> <p style="text-align: center;">30</p> <p style="text-align: center;">F-E,S-E</p> <p style="text-align: center;">A</p> |
| <ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments | <p style="text-align: center;">Not applicable.</p> |

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: SX AR-P 3500/8

(Contd. of page 8)

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category**

3

· **Tunnel restriction code**

D/E

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1993 FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE), 3, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: (Substances not listed)**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c** FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **VOC (EU)** 763.5-763.6 g/l

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· **Disclaimer**

This safety data sheet contains only safety relevant information. The information is based on the state of our knowledge at the time of revision, however, it does not constitute a guarantee of product properties, product information or product specifications and does not establish a contractual legal relationship. This document is only valid in its unchanged form. In the event of changes by third parties, the exhibitor accepts no responsibility for form and content or for any damages or claims arising from such changes. The information is not transferable to other products. If the product named in this safety data sheet is mixed, blended or processed with other materials or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise. The data sheet does not release the user from the obligation to ensure that he acts in accordance with all regulations in connection with his activity.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H228 Flammable solid.

H242 Heating may cause a fire.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 1.1 (replaces version 1.0)

Revision: 12.12.2021

Trade name: SX AR-P 3500/8

(Contd. of page 9)

*H335 May cause respiratory irritation.**H336 May cause drowsiness or dizziness.**H411 Toxic to aquatic life with long lasting effects.**H412 Harmful to aquatic life with long lasting effects.*

- **Department issuing SDS:** Quality Management department

- **Contact:** MSDS authorized Person

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Sol. 1: Flammable solids – Category 1

Self-react. C: Self-reactive substances and mixtures – Type C/D

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3