



Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

 Printing date 12.12.2021
 Version number 1.0
 Revision: 12.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SX AR-P 5000/82 series
- · Article number: SX AR-P 5000/82.7, SX AR-P 5000/82.11
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

 $\cdot \textit{Application of the substance / the mixture}$

Intermediate product for the electronics industry. For industrial and commercial use only.

- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Allresist GmbH Am Biotop 14 15344 Strausberg GERMANY

E-Mail: info@allresist.de Tel.: +49 3341 35 93 0

- · Further information obtainable from: Sales
- 1.4 Emergency telephone number:

Poison center of the Charité Berlin:

+4930 30686700

E-Mail: giftnotruf@charite.de

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Repr. 1A H360Df May damage the unborn child. Suspected of damaging fertility.



Eye Dam. 1 H318 Causes serious eye damage.



(Contd. on page 2)

Printing date 12.12.2021 Version number 1.0 Revision: 12.12.2021

Trade name: SX AR-P 5000/82 series

(Contd. of page 1)

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS05

· Signal word Danger

· Hazard-determining components of labelling:

N-Ethyl-2-Pyrrolidone

2-methoxy-1-methylethyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H360Df May damage the unborn child. Suspected of damaging fertility.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 *Use explosion-proof [electrical/ventilating/lighting] equipment.*

Wear protective gloves/protective clothing/eye protection/face protection/hearing P280

protection.

P310 Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label). P321

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 12.12.2021 Version number 1.0 Revision: 12.12.2021

Trade name: SX AR-P 5000/82 series

	(Contd. of page 2
· Dangerous compone	ents:	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	≥50-≤100%
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226; 🕠 STOT SE 3, H336	
CAS: 2687-91-4	N-Ethyl-2-Pyrrolidone	≥10-≤25%
EINECS: 220-250-6	♦ Repr. 1A, H360Df; ♦ Eye Dam. 1, H318	
CAS: 129197-50-8	Poly[(1,3-dihydro-1,3-dioxo-2H-isoindole-2,5-diyl)[2,2,2-trifluoro-1-	≥10-≤25%
	(trifluoromethyl)ethylidene](1,3-dihydro-1,3-dioxo-2H-isoindole-5,2-	
	diyl)-1,4-phenylenecarbonylimino(6-hydroxy-1,3-phenylene)[2,2,2-	
	trifluoro-1-(trifluoromethyl)ethylidene](4-hydroxy-1,3-phenylene)	
	iminocarbonyl-1,4-phenylene]	
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 68510-93-0	Naphthochinondiazid	≥2.5-<10%
EINECS: 270-931-7	🍅 Flam. Sol. 1, H228; Self-react. C, H242; 🕠 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	
CAS: 1143-72-2	2,3,4-trihydroxybenzophenone	≥0-<2.5%
EINECS: 214-540-1	💠 Skin Irrit. 2, H315; STOT SE 3, H335; Aquatic Chronic 3, H412	
Additional informati	ion: For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

Trade name: SX AR-P 5000/82 series

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Recommended storage temperature: 8-12°C
- · Storage class (TRGS): 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingre	· Ingredients with limit values that require monitoring at the workplace:		
108-6	108-65-6 2-methoxy-1-methylethyl acetate		
	Short-term value: 548 mg/m³, 100 ppm		
	Long-term value: 274 mg/m³, 50 ppm		
	Sk		

•	DNELs
---	--------------

108-65-6 2	-methoxy-1-methylethyl acetate		
Oral	DNEL Long-term - oral, systemic effects	1.67 mg/kg_bw/day (rat)	
Dermal	DNEL Long-term – dermal, systemic effects	153.5 mg/kg_bw/day (rat)	
Inhalative	DNEL long-term - inhalation local effects	$33 \text{ mg/m}^3 \text{ (rat)}$	
	DNEL Long-term – inhalation, systemic effects	275 mg/m³/day (rat)	
	DNEL Acute - inhalation, local effects	$2,420 \text{ mg/m}^3 \text{ (rat)}$	
2687-91-4 N-Ethyl-2-Pyrrolidone			
Oral	DNEL Long-term - oral, systemic effects	0.5 mg/kg_bw/day (general public)	
Dermal	DNEL Long-term – dermal, systemic effects	4 mg/kg_bw/day (Worker)	
		0.5 mg/kg_bw/day (general public)	
Inhalative	DNEL long-term - inhalation local effects	10.05 mg/m³ (Worker)	
		1.2 mg/m³ (general public)	
	DNEL Long-term – inhalation, systemic effects	16.75 mg/m³/day (Worker)	
		1 mg/m³/day (BEv)	

· PNECs

108-65-6 2-methoxy-1-methylethyl acetate

PNEC short term, fresh water 0.635 mg/l (Aquatic organisms)

(Contd. on page 5)

Printing date 12.12.2021 Version number 1.0 Revision: 12.12.2021

Trade name: SX AR-P 5000/82 series

	(Contd. of page 4)
PNEC short term, sea water	0.0635 mg/l (Aquatic organisms)
PNEC short term, sewage plant	100 mg/l (Aquatic organisms)
PNEC short term fresh water sediment	3.29 mg/kg (Aquatic organisms)
PNEC short term soil	0.29 mg/kg (Aquatic organisms)
PNEC short term sea water sediment	0.329 mg/kg (Aquatic organisms)
PNEC short term, intermittent releases	6.35 mg/l (Aquatic organisms)
2687-91-4 N-Ethyl-2-Pyrrolidone	
PNEC short term, fresh water	0.25 mg/l (Aquatic organisms)
PNEC short term, sea water	0.025 mg/l (Aquatic organisms)
PNEC short term, sewage plant	10 mg/l (Aquatic organisms)
PNEC short term fresh water sediment	1.25 mg/kg (Aquatic organisms)
PNEC short term soil	0.104 mg/kg (teresstric organismens)
PNEC short term sea water sediment	0.125 mg/kg (Aquatic organisms)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 12.12.2021 Version number 1.0 Revision: 12.12.2021

Trade name: SX AR-P 5000/82 series

(Contd. of page 5)

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Ddour threshold:
Fluid
Red-brown
Ester-like
Not determined.

· Melting point/freezing point: -66 °C

Boiling point or initial boiling point and boiling

range 145 °C

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: 1.5 Vol %
 · Upper: 10.8 Vol %
 · Flash point: 46 °C

· Auto-ignition temperature: Product is not selfigniting.

• **Decomposition temperature:** Not determined.

• pH Mixture is non-soluble (in water).

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

·Solubility

water: Not miscible or difficult to mix.

• Partition coefficient n-octanol/water (log value) Not determined. • Vapour pressure at 20 °C: 3.1 hPa

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

9.2 Other information

· Appearance:

· Form: Fluid · Important information on protection of health and

environment, and on safety.

· Ignition temperature: 315 °C

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

• Organic solvents: 57.4-64.6 % • VOC (EC) 57.37-64.55 %

· Change in condition

· Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void

(Contd. on page 7)

Printing date 12.12.2021 Version number 1.0 Revision: 12.12.2021

Trade name: SX AR-P 5000/82 series

(Contd. of page 6)

· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable	
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

· Desensitised explosives

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Void

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Tiente towery
· LD/LC50 values relevant for classification:
108-65-6 2-methoxy-1-methylethyl acetate
Oral LD50 8,532 mg/kg (rat)
2687-91-4 N-Ethyl-2-Pyrrolidone
Oral LD50 3,200 mg/kg (rat)
Dermal LD50 >2,000 mg/kg (rat)
68510-93-0 Naphthochinondiazid
Oral LD50 >5,000 mg/kg (rat)
. Skin corresion/irritation Causes skin irritation

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Reproductive toxicity May damage the unborn child. Suspected of damaging fertility.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

Printing date 12.12.2021 Version number 1.0 Revision: 12.12.2021

Trade name: SX AR-P 5000/82 series

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

108-65-6 2-methoxy-1-methylethyl acetate		
Inhalative	LC50 (4h)	35.7 mg/l (rat)
	LC50 (96h) mg/ltr.	>100 mg/ltr (Fish)
		100-180 mg/ltr (Oncorhynchus mykiss)
		134 mg/ltr (rainbow trout)
	EC50 (48h)	408 mg/l (daphnia)
	ErC50 (96h)	>1,000 mg/ltr (algae)
	NOEC	100 mg/ml (daphnia)
2687-91-4	N-Ethyl-2-Pyrrolid	one
	LC50 (96h) mg/ltr.	464-999 mg/ltr (Zebrafisch)
	EC50 (48h)	>104 mg/l (daphnia)
	ErC (72h)	>101 mg/l (algae)

· 12.2 Persistence and degradability

108-65-6 2-methoxy-1-methylethyl acetate 90 %

· Method

108-65-6 2-methoxy-1-methylethyl acetate 83

· 12.3 Bioaccumulative potential

2687-91-4 N-Ethyl-2-Pyrrolidone -0,2

- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

GE

 Printing date 12.12.2021
 Version number 1.0
 Revision: 12.12.2021

Trade name: SX AR-P 5000/82 series

(Contd. of page 8)

14.1 UN number or ID number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name ADR IMDG, IATA	1993 FLAMMABLE LIQUID, N.O.S. (2-methoxy-methylethyl acetate) FLAMMABLE LIQUID, N.O.S. (2-methoxy-methylethyl acetate)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
14.7 Maritime transport in bulk according to IM instruments	10 Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	Maximum net quantity per outer packaging. 1000 mt 3 D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (2-METHOX 1-METHYLETHYL ACETATE), 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: (Substances not listed)

None of the ingredients is listed.

(Contd. on page 10)

Printing date 12.12.2021 Version number 1.0 Revision: 12.12.2021

Trade name: SX AR-P 5000/82 series

(Contd. of page 9)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · VOC (EU) 573.7-645.5 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Disclaimer

This safety data sheet contains only safety relevant information. The information is based on the state of our knowledge at the time of revision, however, it does not constitute a guarantee of product properties, product information or product specifications and does not establish a contractual legal relationship. This document is only valid in its unchanged form. In the event of changes by third parties, the exhibitor accepts no responsibility for form and content or for any damages or claims arising from such changes. The information is not transferable to other products. If the product named in this safety data sheet is mixed, blended or processed with other materials or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise. The data sheet does not release the user from the obligation to ensure that he acts in accordance with all regulations in connection with his activity.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H242 Heating may cause a fire.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

H360Df May damage the unborn child. Suspected of damaging fertility.

H412 Harmful to aquatic life with long lasting effects.

- · Department issuing SDS: Quality Management department
- · Contact: MSDS authorized Person
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Sol. 1: Flammable solids – Category 1

Self-react. C: Self-reactive substances and mixtures – Type C/D

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 1A: Reproductive toxicity - Category 1A

(Contd. on page 11)

Printing date 12.12.2021 Version number 1.0 Revision: 12.12.2021

Trade name: SX AR-P 5000/82 series

(Contd. of page 10)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

CD