



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 15.0 (replaces version 1.0)

Revision: 12.12.2021

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****· 1.1 Product identifier****· Trade name:** X AR 300-74 / 1**· Article number:** X AR 300-74/1**· CAS Number:**

100-41-4

**· EC number:**

202-849-4

**· Index number:**

601-023-00-4

**· 1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**· Application of the substance / the mixture**

Intermediate product for the electronics industry. For industrial and commercial use only.

**· 1.3 Details of the supplier of the safety data sheet****· Manufacturer/Supplier:**Allresist GmbH  
Am Biotop 14  
15344 Strausberg  
GERMANYE-Mail: [info@allresist.de](mailto:info@allresist.de)

Tel.: +49 3341 35 93 0

**· Further information obtainable from: Sales****· 1.4 Emergency telephone number:**

Poison center of the Charité Berlin:

+4930 30686700

E-Mail: [gifnotruf@charite.de](mailto:gifnotruf@charite.de)**SECTION 2: Hazards identification****· 2.1 Classification of the substance or mixture****· Classification according to Regulation (EC) No 1272/2008**

flame

Flam. Liq. 2      H225 Highly flammable liquid and vapour.



health hazard

STOT RE 2      H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Asp. Tox. 1      H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 15.0 (replaces version 1.0)

Revision: 12.12.2021

Trade name: X AR 300-74 / 1

(Contd. of page 1)



Acute Tox. 4      H332 Harmful if inhaled.

Aquatic Chronic 3      H412 Harmful to aquatic life with long lasting effects.

#### · 2.2 Label elements

##### · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

##### · Hazard pictograms



GHS02    GHS07    GHS08

##### · Signal word *Danger*

##### · Hazard-determining components of labelling:

*ethylbenzene*

##### · Hazard statements

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

##### · Precautionary statements

P101      If medical advice is needed, have product container or label at hand.

P102      Keep out of reach of children.

P103      Read carefully and follow all instructions.

P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241      Use explosion-proof [electrical/ventilating/lighting] equipment.

P260      Do not breathe dust/fume/gas/mist/vapours/spray.

P273      Avoid release to the environment.

P280      Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310      IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331      Do NOT induce vomiting.

P303+P361+P353      IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340      IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P405      Store locked up.

P501      Dispose of contents/container in accordance with local/regional/national/international regulations.

##### · 2.3 Other hazards

##### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.· **vPvB:** Not applicable.

GB

(Contd. on page 3)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 15.0 (replaces version 1.0)

Revision: 12.12.2021

Trade name: X AR 300-74 / 1

(Contd. of page 2)

### SECTION 3: Composition/information on ingredients

- **3.1 Substances**
- **CAS No. Description**  
100-41-4 ethylbenzene
- **Identification number(s)**
- **EC number:** 202-849-4
- **Index number:** 601-023-00-4

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 15.0 (replaces version 1.0)

Revision: 12.12.2021

Trade name: X AR 300-74 / 1

(Contd. of page 3)

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Recommended storage temperature:** 10-22°C
- **Storage class (TRGS):** 3
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

##### · **Ingredients with limit values that require monitoring at the workplace:**

##### **100-41-4 ethylbenzene**

WEL	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm
	Long-term value: 441 mg/m <sup>3</sup> , 100 ppm
Sk	

##### · **DNELs**

##### **100-41-4 ethylbenzene**

Dermal	DNEL Long-term – dermal, systemic effects	180 mg/kg_bw/day (Worker)
Inhalative	DNEL Long-term – inhalation, systemic effects	77 mg/m <sup>3</sup> /day (Worker)
	DNEL Acute - inhalation, local effects	293 mg/m <sup>3</sup> (Worker)

##### · **PNECs**

##### **100-41-4 ethylbenzene**

PNEC short term, fresh water	0.1 mg/l (Aquatic organisms)
PNEC short term, sea water	0.01 mg/l (Aquatic organisms)
PNEC short term fresh water sediment	13.7 mg/kg (Aquatic organisms)
PNEC short term soil	2.68 mg/kg (terrestrial organisms)
PNEC short term sea water sediment	1.37 mg/kg (Aquatic organisms)
PNEC short term, intermittent releases	0.1 mg/l (Aquatic organisms)
PNEC secondary poisoning	0.02 mg/kg KG/d (Aquatic organisms)

· **Additional information:** The lists valid during the making were used as basis.

#### · **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 15.0 (replaces version 1.0)

Revision: 12.12.2021

Trade name: X AR 300-74 / 1

(Contd. of page 4)

- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection**



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Fluid
- **Colour:** Colourless
- **Odour:** Aromatic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** -94.4 °C
- **Boiling point or initial boiling point and boiling range** 136 °C
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** 1 Vol %
- **Upper:** 7.8 Vol %
- **Flash point:** 15 °C
- **Auto-ignition temperature:** Not determined.
- **Decomposition temperature:** Not determined.
- **pH** Mixture is non-soluble (in water).
- **Viscosity:**
- **Kinematic viscosity at 20 °C** 1.23 mm<sup>2</sup>/s
- **Dynamic at 20 °C:** 0.63 mPas

(Contd. on page 6)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 15.0 (replaces version 1.0)

Revision: 12.12.2021

Trade name: X AR 300-74 / 1

(Contd. of page 5)

· <b>Solubility</b>	
· water at 20 °C:	0.2 g/l
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	9.5 hPa
· <b>Density and/or relative density</b>	
· Density at 20 °C:	0.87 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.

· <b>9.2 Other information</b>	
· <b>Appearance:</b>	
· Form:	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· Ignition temperature:	430 °C
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Solvent content:</b>	
· Organic solvents:	100.0 %
· VOC (EC)	100.00 %
· <b>Change in condition</b>	
· Evaporation rate	Not determined.

· <b>Information with regard to physical hazard classes</b>	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 7)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 15.0 (replaces version 1.0)

Revision: 12.12.2021

Trade name: X AR 300-74 / 1

(Contd. of page 6)

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity Harmful if inhaled.**

- **LD/LC50 values relevant for classification:**

Oral	Acute Toxicity Estimate of ingredient (ATE) oral	>5,000 mg/kg (Worker)
Dermal	Schätzwerte akuter Toxizität	>2,000 mg/kg (Worker)
Inhalative	Acute toxicity Estimate inhalative (4h)	>20 mg/l (Worker)

#### 100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	15,400 mg/kg (rabbit)

- **STOT-repeated exposure** May cause damage to the hearing organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

Substance is not listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

#### 100-41-4 ethylbenzene

Inhalative	LC50 (4h)	17.2 mg/l (rat)
	LC50 (96h) mg/ltr.	11-18 mg/ltr (Oncorhynchus mykiss)
	EC50 (48h)	mg/l (daphnia)
	EC50 (72h)	2.6-11.3 mg/l (Pseudokirchneriella subcapitata)
	EC50 (96h) mg/ltr	1.7-7.6 mg/ltr (Pseudokirchneriella subcapitata)
	EC50 (24h)	96 mg/kg (Microorganism)
	EC50 (30min.)	9.68 mg/l (Microorganism)

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects** No further relevant information available.

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

GB

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 15.0 (replaces version 1.0)

Revision: 12.12.2021


Trade name: X AR 300-74 / 1

(Contd. of page 7)

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |   |
|---|---|
| · <b>14.1 UN number or ID number</b><br>· <b>ADR, IMDG, IATA</b>  | UN1175  |
| · <b>14.2 UN proper shipping name</b><br>· <b>ADR</b><br>· <b>IMDG, IATA</b>  | 1175 ETHYLBENZENE<br>ETHYLBENZENE   |
| · <b>14.3 Transport hazard class(es)</b><br>· <b>ADR, IMDG, IATA</b>  | <br>· <b>Class</b> 3 Flammable liquids.<br>· <b>Label</b> 3 |
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>   | II  |
| · <b>14.5 Environmental hazards:</b>  | Not applicable.   |
| · <b>14.6 Special precautions for user</b><br>· <b>Hazard identification number (Kemler code):</b><br>· <b>EMS Number:</b><br>· <b>Stowage Category</b> | Warning: Flammable liquids.<br>33<br>F-E,S-D<br>B   |
| · <b>14.7 Maritime transport in bulk according to IMO instruments</b>   | Not applicable.   |
| · <b>Transport/Additional information:</b>  |   |
| · <b>ADR</b><br>· <b>Limited quantities (LQ)</b><br>· <b>Excepted quantities (EQ)</b>   | 1L<br>Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml                         |
| · <b>Transport category</b><br>· <b>Tunnel restriction code</b>   | 2<br>D/E  |
| · <b>IMDG</b><br>· <b>Limited quantities (LQ)</b><br>· <b>Excepted quantities (EQ)</b>  | 1L<br>Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml                         |

(Contd. on page 9)

GB



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 12.12.2021

Version number 15.0 (replaces version 1.0)

Revision: 12.12.2021

Trade name: X AR 300-74 / 1

(Contd. of page 8)

· UN "Model Regulation":

UN 1175 ETHYLBENZENE, 3, II

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**  
(Substances not listed)

Substance is not listed.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** Substance is not listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **National regulations:**
- **VOC (EU)** 870.0 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

· **Disclaimer**

This safety data sheet contains only safety relevant information. The information is based on the state of our knowledge at the time of revision, however, it does not constitute a guarantee of product properties, product information or product specifications and does not establish a contractual legal relationship. This document is only valid in its unchanged form. In the event of changes by third parties, the exhibitor accepts no responsibility for form and content or for any damages or claims arising from such changes. The information is not transferable to other products. If the product named in this safety data sheet is mixed, blended or processed with other materials or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise. The data sheet does not release the user from the obligation to ensure that he acts in accordance with all regulations in connection with his activity.

· **Department issuing SDS:** Quality Management department

· **Contact:** MSDS authorized Person

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3