ALLRESIST



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.12.2021

Version number 4.1 (replaces version 4.0)

Revision: 21.12.2021

Page 1/9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: <u>AR 300-80 new</u>
- Article number: AR 300-80 new
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture
- Intermediate product for the electronics industry. For industrial and commercial use only.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:
- Allresist GmbH Am Biotop 14 15344 Strausberg GERMANY

E-Mail: info@allresist.de Tel.: +49 3341 35 93 0

- · Further information obtainable from: Sales
- 1.4 Emergency telephone number: Poison center of the Charité Berlin: +4930 30686700 E-Mail: giftnotruf@charite.de

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 21.12.2021

Version number 4.1 (replaces version 4.0)

Revision: 21.12.2021

Har and alot a car	(Contd. of page
Hazard pictogra	ims
<u>< {}} < !</u>	
GHS02 GHS	507
Signal word Wa	rning
Hazard-determi	ning components of labelling:
	thylethyl acetate
Hazard stateme	nts
H226 Flammabl	le liquid and vapour.
H336 May cause	e drowsiness or dizziness.
Precautionary s	tatements
P101	<i>If medical advice is needed, have product container or label at hand.</i>
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. I smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P3	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/internation regulations.
2.3 Other hazar	

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	2-methoxy-1-methylethyl acetate	50-100%
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
CAS: 6843-66-9	dimethoxydiphenylsilane	≤2.5%
	𝒱 Skin Irrit. 2, H315	
• Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

• After skin contact: Immediately rinse with water.

• After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3) GB

Printing date 21.12.2021

Version number 4.1 (replaces version 4.0)

Revision: 21.12.2021

Trade name: AR 300-80 new

• **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.*

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 10-22°C
- Storage class (TRGS): 3
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

(Contd. of page 2)

Printing date 21.12.2021

Version number 4.1 (replaces version 4.0)

Revision: 21.12.2021

(Contd. of page 3)

Trade name: AR 300-80 new

· 8.1 Control parameters

SECTION 8: Exposure controls/personal protection

· Ingredients with limit values that requ		he workplace:	
108-65-6 2-methoxy-1-methylethyl acc			
WEL Short-term value: 548 mg/m ³ , 10 Long-term value: 274 mg/m ³ , 50 Sk			
· DNELs			
108-65-6 2-methoxy-1-methylethyl acc	etate		
Oral DNEL Long-term - oral, sys		1.67 mg/kg bw/day (rat)	
Dermal DNEL Long-term – dermal,		153.5 mg/kg bw/day (rat)	
Inhalative DNEL long-term - inhalation		33 mg/m^3 (rat)	
DNEL Long-term – inhalati			
DNEL Acute - inhalation, lo		$2,420 \text{ mg/m}^3 \text{ (rat)}$	
· PNECs		<u> </u>	
108-65-6 2-methoxy-1-methylethyl acc	etate		
PNEC short term, fresh water	0.635 mg/l (Aquati	ic organisms)	
PNEC short term, sea water	0.0635 mg/l (Aqua		
PNEC short term, sewage plant	100 mg/l (Aquatic		
PNEC short term fresh water sediment	PNEC short term fresh water sediment 3.29 mg/kg (Aquatic organisms)		
PNEC short term soil 0.29 mg/kg (Aquatic organisms)		ic organisms)	
PNEC short term sea water sediment 0.329 mg/kg (Aq			
PNEC short term, intermittent releases 6.35 mg/l (Aquatic organisms)			
• Additional information: The lists valid	during the making	were used as basis.	
 8.2 Exposure controls Appropriate engineering controls No f Individual protection measures, such a General protective and hygienic measures, mediately remove all soiled and cont Wash hands before breaks and at the endities Respiratory protection: In case of brief exposure or low pollutit use self-contained respiratory protective Hand protection 	as personal protecti ures: taminated clothing nd of work. on use respiratory j		
		the product/ the substance/ the preparation. erial can be given for the product/ the preparation/	
	consideration of th	he penetration times, rates of diffusion and the	

degradation · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

GB

Printing date 21.12.2021

Version number 4.1 (replaces version 4.0)

Revision: 21.12.2021

Trade name: AR 300-80 new

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties • 9.1 Information on basic physical and chemical properties · General Information · Physical state Fluid · Colour: Colourless · Odour: Ester-like · Odour threshold: Not determined. • *Melting point/freezing point:* Undetermined. · Boiling point or initial boiling point and boiling 145 °C range · Flammability *Not applicable.* · Lower and upper explosion limit · Lower: 1.5 Vol % · Upper: 10.8 Vol % · Flash point: 46 °C Product is not selfigniting. • Auto-ignition temperature: • Decomposition temperature: Not determined. · pH at 20 °C 6-8 · Viscosity: $1.23 \text{ mm}^2/\text{s}$ • Kinematic viscosity at 20 °C Not determined. · Dynamic: · Solubility water at 20 °C: $220 \, g/l$ Not determined. · Partition coefficient n-octanol/water (log value) 3.37 hPa • Vapour pressure at 20 °C: · Density and/or relative density • Density at 20 °C: $l g/cm^3$ · Relative density Not determined. Not determined. · Vapour density • 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. 315 °C (108-65-6 2-methoxy-1-methylethyl acetate) · Ignition temperature: Product is not explosive. However, formation of · Explosive properties: explosive air/vapour mixtures are possible. · Solvent content: 98.0 % · Organic solvents: 98.00 % · VOC (EC) · Change in condition · Evaporation rate Not determined. (Contd. on page 6) GB

Printing date 21.12.2021

Version number 4.1 (replaces version 4.0)

Revision: 21.12.2021

Trade name: AR 300-80 new

		(Contd. of page
Information with regard to physical hazard	classes	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 • Acute toxicity

· LD/LC50	values relevant for classification:	
Oral	Acute Toxicity Estimate of ingredient (ATE) oral	>5,000 mg/kg (Worker)
Dermal	Schätzwerte akuter Toxicität	>2,000 mg/kg (Worker)
Inhalative	Acute toxicity Estimate inhalative (4h)	>20 mg/l (Worker)
108-65-62	P-methoxy-1-methylethyl acetate	
Oral	LD50	8,532 mg/kg (rat)
6843-66-9	dimethoxydiphenylsilane	
Oral	LD50	>2,000 mg/kg (rat)
	gle exposure May cause drowsiness or dizziness. mation on other hazards	
· Endocrine	disrupting properties	
None of the	e ingredients is listed.	
		GB

(Contd. on page 7)

Printing date 21.12.2021

Version number 4.1 (replaces version 4.0)

Revision: 21.12.2021

Trade name: AR 300-80 new

ity: ethoxy-1-methy 550 (4h)	ylethyl acetate 35.7 mg/l (rat)
ethoxy-1-methy C50 (4h)	· · ·
C50 (4h)	· · ·
. ,	35.7 mg/l (rat)
'50 (96h) mg/ltr	r. >100 mg/ltr (Fish)
	100-180 mg/ltr (Oncorhynchus mykiss)
	134 mg/ltr (rainbow trout)
C50 (48h)	408 mg/l (daphnia)
C50 (96h)	>1,000 mg/ltr (algae)
DEC	100 mg/ml (daphnia)
ce and degrada	lability
ethoxy-1-methy	ylethyl acetate 90 %
ethoxv-1-methv	ylethyl acetate 83
verse effects No ological inform :: class 1 (German	n substances with endocrine disrupting properties. To further relevant information available. nation: an Regulation) (Self-assessment): slightly hazardous for water aduct or large quantities of it to reach ground water, water course or sewa
unununeu prou	auci or large quantities of it to reach ground water, water course or sewa
13: Disposal	l considerations
eatment method tion	
13: 1	Disposa l

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1993
 14.2 UN proper shipping name ADR 	1993 FLAMMABLE LIQUID, N.O.S. (2-methoxy-1-
· IMDG, IATA	methylethyl acetate) FLAMMABLE LIQUID, N.O.S. (2-methoxy-1- methylethyl acetate)

(Contd. on page 8)

⁻ GB -

Printing date 21.12.2021

Version number 4.1 (replaces version 4.0)

Revision: 21.12.2021

Trade name: AR 300-80 new

	(Contd. of page
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number: Stowage Category	<i>F-E,<u>S-E</u> A</i>
0 0 0	
14.7 Maritime transport in bulk according to IM instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
Tunner out onton out	Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 D/E
	שוש
IMDG Limited quantities (LQ)	5L
Excepted quantities (EQ)	SL Code: E1
Excepted quantines (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (2-METHOX)
8	I-METHYLETHYL ACETATE), 3, III

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: (Substances not listed)

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

• VOC (EU) 980.0 g/l

(Contd. on page 9)

⁻ GB

Printing date 21.12.2021

Version number 4.1 (replaces version 4.0)

Revision: 21.12.2021

Trade name: AR 300-80 new

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 8)

SECTION 16: Other information

· Disclaimer

This safety data sheet contains only safety relevant information. The information is based on the state of our knowledge at the time of revision, however, it does not constitute a guarantee of product properties, product information or product specifications and does not establish a contractual legal relationship. This document is only valid in its unchanged form. In the event of changes by third parties, the exhibitor accepts no responsibility for form and content or for any damages or claims arising from such changes. The information is not transferable to other products. If the product named in this safety data sheet is mixed, blended or processed with other materials or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise. The data sheet does not release the user from the obligation to ensure that he acts in accordance with all regulations in connection with his activity.

· Relevant phrases

H226 Flammable liquid and vapour. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.

· Department issuing SDS: Quality Management department

· Contact: MSDS authorized Person

· Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3