ALLRESIST



Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.10.2022 Version number 1.0 Revision: 24.10.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: AR-P 3500 series
- · Article number: AR-P 3510, AR-P 3540
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

 $No\ further\ relevant\ information\ available.$

· Application of the substance / the mixture

Intermediate product for the electronics industry. For industrial and commercial use only.

- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Allresist GmbH Am Biotop 14 15344 Strausberg GERMANY

E-Mail: info@allresist.de Tel.: +49 3341 35 93 0

- · Further information obtainable from: Sales
- · 1.4 Emergency telephone number: Poison center of the Charité Berlin:

+4930 30686700

E-Mail: giftnotruf@charite.de

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.10.2022 Version number 1.0 Revision: 24.10.2022

Trade name: AR-P 3500 series

· Hazard pictograms





· Signal word Warning

Hazard-determining components of labelling:

2-methoxy-1-methylethyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

Read carefully and follow all instructions. P103

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

smoking.

P241 *Use explosion-proof [electrical/ventilating/lighting] equipment.*

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

	Dangerous components:				
Γ	CAS: 108-65-6 2-methoxy-1-methylethyl acetate				
	EINECS: 203-603-9	🚸 Flam. Liq. 3, H226; 🕠 STOT SE 3, H336			
ſ		- · · · · · · · · · · · · · · · · · · ·	≥2.5-<10%		
	EINECS: 270-931-7	🌣 Flam. Sol. 1, H228; Self-react. C, H242; 🗘 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412			

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available. (Contd. on page 3)

Printing date 24.10.2022 Version number 1.0 Revision: 24.10.2022

Trade name: AR-P 3500 series

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Recommended storage temperature: 10-18°C
- · Storage class (TRGS): 3
- · 7.3 Specific end use(s) No further relevant information available.

GB

Printing date 24.10.2022 Version number 1.0 Revision: 24.10.2022

Trade name: AR-P 3500 series

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

· DNELs

108-65-6 2-methoxy-1-methylethyl acetate

Oral	DNEL Long-term - oral, systemic effects	1.67 mg/kg_bw/day (rat)
Dermal	DNEL Long-term – dermal, systemic effects	153.5 mg/kg_bw/day (rat)
Inhalative	DNEL long-term - inhalation local effects	33 mg/m³ (rat)
	DNEL Long-term – inhalation, systemic effects	275 mg/m³/day (rat)
	DNEL Acute - inhalation, local effects	$2,420 \text{ mg/m}^3 \text{ (rat)}$

· PNECs

108-65-6 2-methoxy-1-methylethyl acetate

PNEC short term, fresh water	0.635 mg/l (Aquatic organisms)
PNEC short term, sea water	0.0635 mg/l (Aquatic organisms)
	100 mg/l (Aquatic organisms)
PNEC short term fresh water sediment	
PNEC short term soil	0.29 mg/kg (Aquatic organisms)
PNEC short term sea water sediment	0.329 mg/kg (Aquatic organisms)
PNEC short term, intermittent releases	6.35 mg/l (Aquatic organisms)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 24.10.2022 Version number 1.0 Revision: 24.10.2022

Trade name: AR-P 3500 series

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:
Fluid
Brown
Ester-like
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range 145 °C Flammability Flammable.

· Lower and upper explosion limit

Lower: 1.5 Vol %
 Upper: 10.8 Vol %
 Flash point: 46 °C

• **Decomposition temperature:** Not determined.

• pH Mixture is non-soluble (in water).

· Viscosity:

· Kinematic viscosity Not determined.

· Viscosity @100°C:

· **Dynamic:** Not determined.

·Solubility

water: Fully miscible.
Partition coefficient n-octanol/water (log value)
Vapour pressure at 20 °C: 3.1 hPa

· Density and/or relative density

Density: Not determined.
 Relative density Not determined.
 Density (@15°C) Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

• Organic solvents: 64.4-68 % • VOC (EC) 64.41-68 %

· Change in condition

· Evaporation rate Not determined.

(Contd. on page 6)

Printing date 24.10.2022 Version number 1.0 Revision: 24.10.2022

Trade name: AR-P 3500 series

		(Contd. of page 5)		
· Information with regard to physical hazard classes				
· Explosives	Void			
· Flammable gases	Void			
· Aerosols	Void			
· Oxidising gases	Void			
· Gases under pressure	Void			
· Flammable liquids	Flammable liquid and vapour.			
· Flammable solids	Void			
· Self-reactive substances and mixtures	Void			
· Pyrophoric liquids	Void			
· Pyrophoric solids	Void			
· Self-heating substances and mixtures	Void			
· Substances and mixtures, which emit flamma	ıble			
gases in contact with water	Void			
· Oxidising liquids	Void			
· Oxidising solids	Void			
· Organic peroxides	Void			
· Corrosive to metals	Void			
Desensitised explosives	Void			

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

LD/LC50 values relevant for classification:				
108-65-6 2	l-methylethyl acetate			
Oral	LD50	8,532 mg/kg (rat)		
Inhalative	LC50 (4h)	35.7 mg/l (rat)		
68510-93-	0 Naphthoc	chinondiazid		
Oral	LD50	>5,000 mg/kg (rat)		
· STOT-single exposure May cause drowsiness or dizziness.				

11.2 Information on other hazards

· Endocrine disrupting properties				
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II		
556-67-2	octamethylcyclotetrasiloxane	List II, III		

Trade name: AR-P 3500 series

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:			
108-65-6 2-methoxy-1-methylethyl acetate			
LC50 (96h) mg/ltr.			
	100-180 mg/ltr (Oncorhynchus mykiss)		
	134 mg/ltr (rainbow trout)		
EC50 (48h)	408 mg/l (daphnia)		
ErC50 (96h)	>1,000 mg/ltr (algae)		
NOEC	100 mg/l (daphnia)		

· 12.2 Persistence and degradability

108-65-6 2-methoxy-1-methylethyl acetate 90 %

· Method

108-65-6 2-methoxy-1-methylethyl acetate 83

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1993
· 14.2 UN proper shipping name	
· ADR	1993 FLAMMABLE LIQUID, N.O.S. (2-methoxy-methylethyl acetate)
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (2-methoxy-methylethyl acetate)

(Contd. on page 8)

(Contd. of page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.10.2022 Version number 1.0 Revision: 24.10.2022

Trade name: AR-P 3500 series

(Conta. of page 7)			
			٦
			١
			-
			-
			-
			-
			-
			-
			-
			-
			-
			-
			-
			┥
			-
			-
			-
			-
			-
			T
			4
			١

14.3	Transport	hazard	class(es)
	I i iii i i i i i i i i i i i i i i i i		000000

· ADR, IMDG, IATA



3 Flammable liquids. · Class · Label

· 14.4 Packing group

· ADR, IMDG, IATA III

· 14.5 Environmental hazards: Not applicable.

· 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30 · EMS Number: F-E,S-E· Stowage Category

· 14.7 Maritime transport in bulk according to IMO

Not applicable. instruments

· Transport/Additional information:

 $\cdot ADR$

5L· Limited quantities (LQ) Code: E1 · Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category D/E· Tunnel restriction code

 \cdot IMDG

· Limited quantities (LQ) 5LCode: E1 Excepted quantities (EQ)

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN 1993 FLAMMABLE LIQUID, N.O.S. (2-METHOXY-· UN "Model Regulation": 1-METHYLETHYL ACETATE), 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: (Substances not listed)

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · VOC (EU) 644.1-680 g/l

(Contd. on page 9)

Trade name: AR-P 3500 series

(Contd. of page 8)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Disclaimer

This safety data sheet contains only safety relevant information. The information is based on the state of our knowledge at the time of revision, however, it does not constitute a guarantee of product properties, product information or product specifications and does not establish a contractual legal relationship. This document is only valid in its unchanged form. In the event of changes by third parties, the exhibitor accepts no responsibility for form and content or for any damages or claims arising from such changes. The information is not transferable to other products. If the product named in this safety data sheet is mixed, blended or processed with other materials or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise. The data sheet does not release the user from the obligation to ensure that he acts in accordance with all regulations in connection with his activity.

· Relevant phrases

H226 Flammable liquid and vapour.

H228 Flammable solid.

H242 Heating may cause a fire.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Quality Management department

· Contact: MSDS authorized Person

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Sol. 1: Flammable solids - Category 1

Self-react. C: Self-reactive substances and mixtures – Type C/D

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.